

# Cisco Catalyst 9600 Series Switches

---

# Contents

|   |    |
|---|----|
| Introduction  | 3  |
| Product overview  | 4  |
| Platform benefits                                       | 6  |
| Software Policy for Cisco Catalyst 9600 Series Switches | 11 |
| Physical specifications                                 | 16 |
| Ordering information                                    | 21 |
| Product sustainability                                  | 23 |
| Cisco Enhanced Limited Lifetime Hardware Warranty       | 24 |
| Cisco Services  | 25 |
| Cisco Capital   | 26 |
| Document history  | 27 |

---

## Introduction

### Empowering Core Layer and Edge Services with Higher Speeds and Scales

Cisco Catalyst 9600 Series Switches are purpose-built for resiliency at scale with the industry's most comprehensive security and allows your business to grow at the lowest total operational cost. Built upon the foundation of the Catalyst 9000, the Catalyst 9600 Series offers scale and security when always-on is a must.

As a foundational building block for the Cisco Digital Network Architecture, the Catalyst 9600 Series switch help customers simplify complexity, optimize IT, and reduce operational costs by leveraging intelligence, automation and human expertise that no other vendor can deliver regardless of where you are in the intent-based networking journey.

Catalyst 9600 Series Switches provide security features that protects the integrity of the hardware as well as the software and all data that flows through the switch. It provides resiliency that keeps your business up and running seamlessly. Combine that with open APIs of Cisco IOS XE and programmability of the UADP and Silicon1 ASIC technologies, Catalyst 9600 Series switches give you what you need now with investment protection on future innovations.

As the industry's first purpose-built 40,100, 200 and 400 Gigabit Ethernet line of modular switches targeted for the enterprise campus, Catalyst 9600 Series switches deliver unmatched table scale (MAC, route, and Access Control List [ACL]) and buffering for enterprise applications. The Cisco Catalyst 9606R chassis is hardware ready to support a wired switching capacity of up to 25.6 Tbps, with up to 6.4 Tbps of bandwidth per slot. Cisco Catalyst 9600 Series switches support granular port densities that fit diverse campus needs, including nonblocking 40, 100, 200 and 400 Gigabit Ethernet (GE) Quad Small Form Factor Double Density (QSFP-DD), 40 and 100 Gigabit Ethernet (GE) Quad Small Form-Factor Pluggable (QSFP+, QSFP28); 1, 10, and 25 GE Small Form-Factor Pluggable Plus (SFP, SFP+, SFP28); 10G Multigigabit Ethernet (GE) (10G/5G/2.5G/1G/100M/10M) RJ45 copper ports. The switches also support advanced routing and infrastructure services (such as Multiprotocol Label Switching [MPLS] Layer 2 and Layer 3 VPNs, Multicast VPN [MVPN], and Network Address Translation [NAT]); Cisco Software-Defined Access capabilities (such as a host tracking database, cross-domain connectivity, and VPN Routing and Forwarding [VRF]-aware Locator/ID Separation Protocol [LISP]); and network system virtualization with Cisco StackWise® virtual technology that are critical for their placement in the campus core. The Cisco Catalyst 9600 Series also supports foundational high-availability capabilities such as patching, Cisco Nonstop Forwarding with Stateful Switchover (NSF/SSO), redundant platinum-rated power supplies, and fans, while supporting a wide array of optics.

---

## The foundation of Software-Defined Access

The enterprise network lies at the heart of digital transformation. A network that is open, programmable, integrated, and secure maximizes business agility, allowing new business opportunities to be pursued and captured. The Cisco Digital Network Architecture (Cisco DNA) with Software-Defined Access (SD-Access) is the network fabric that powers business.

Cisco SD-Access is an open and extensible, software-driven architecture that accelerates and simplifies your enterprise network operations. SD-Access enables policy-based automation from edge to cloud with foundational capabilities.

## Product overview

### Cisco Catalyst 9600 Series Chassis

- Hardware ready to support up to 25.6 Tbps in wired switching capacity, with up to 6.4 Tbps bandwidth per slot.
- 25.6 Tbps wired switching capacity unleashed with Cisco Catalyst 9600 Series Supervisor Engine 2. Up to 9.6 Tbps in wired switching capacity, with 3 Bpps of forwarding performance with the Cisco Catalyst 9600 Series Supervisor Engine 1.
- Capacity of upto 32 ports of 400G Gigabit Ethernet QSFP-DD ports with the Cisco Catalyst 9600 Series Supervisor Engine 2. Upto 8 non-blocking 400 Gigabit Ethernet QSFP-DD ports supported with current generation Line Cards.
- Up to 48 nonblocking 100 Gigabit Ethernet QSPF28 ports with the Cisco Catalyst 9600 Series Supervisor Engine 1, and upto 128 nonblocking 100 Gigabit Ethernet QSPF28 ports with the Cisco Catalyst 9600 Series Supervisor Engine 2
- Upto 128 nonblocking 40 Gigabit Ethernet QSPF28 ports with the Cisco Catalyst 9600 Series Supervisor Engine 2 and up to 96 nonblocking 40 Gigabit Ethernet QSFP+ ports with the Cisco Catalyst 9600 Series Supervisor Engine 1.
- Up to 256 nonblocking 50G/25G/10G Gigabit Ethernet QSPF28 ports with the Cisco Catalyst 9600 Series Supervisor Engine 2 and upto 192 nonblocking 25 Gigabit Ethernet /10 Gigabit Ethernet SFP28/SFP+ ports with the Cisco Catalyst 9600 Series Supervisor Engine 1.
- Up to 192 non blocking 10G multigigabit (10 Gigabit Ethernet / 5 Gigabit Ethernet / 2.5 Gigabit Ethernet / 1 Gigabit Ethernet / 100 Megabit / 10 Megabit) RJ45 copper ports with the Cisco Catalyst 9600 Series Supervisor Engine 1 Supervisor Engine 2 only supports speeds at and above 10 GBps.
- Platinum-rated AC and DC power supplies.



**Figure 1.**  
Cisco Catalyst 9606R Chassis

## Cisco IOS XE

Cisco IOS XE Software opens a completely new paradigm in network configuration, operation, and monitoring through network automation. Cisco's automation solution is open, standards-based, and extensible across the entire lifecycle of a network device. The various automation mechanisms are outlined below.

- **Automated Device Provisioning** is the ability to automate the process of upgrading software images and installing configuration files on Cisco Catalyst switches when they are being deployed in the network for the first time. Cisco provides turnkey solutions such as Plug and Play and Preboot Execution Environment (PXE) that enable an effortless and automated deployment.
- **API-driven configuration** is available with modern network switches such as Cisco Catalyst 9600 Series switches. It supports a wide range of automation features and provides robust open APIs over NETCONF and RESTCONF using YANG data models for external tools, both off the shelf and custom built, to automatically provision network resources.
- **Granular visibility** enables model-driven telemetry to stream data from a switch to a destination. The data to be streamed is identified through subscription to a data set in a YANG model. The subscribed data set is streamed to the destination at specified intervals. Additionally, Cisco IOS XE enables the push model. It provides near-real-time monitoring of the network, leading to quick detection and rectification of failures.
- **Seamless software upgrades and patching** supports OS resilience. On Cisco Catalyst 9600 Series switches Cisco IOS XE supports hot patching without reboot, which provides fixes for critical bugs and security vulnerabilities between regular maintenance releases. This support lets you add patches without having to wait for the next maintenance release.
- **Trustworthy solutions built with Cisco Trust Anchor Technologies** provide a highly secure foundation for Cisco products. With Cisco Catalyst 9600 Series switches, these technologies enable hardware and software authenticity assurance for supply chain trust and strong mitigation against man-in-the-middle attacks that compromise software and firmware. Trust Anchor capabilities include image signing, Secure Boot, and Cisco Trust Anchor module.

## Platform benefits

**Table 1.** Platform benefits of the Cisco Catalyst 9600 and 9600X

| Model                                   | Catalyst 9600 SUP-1 | Catalyst 9600X SUP-2 |
|---|---------------------|----------------------|
| <b>Resiliency and High Availability</b> |                     |                      |
| Software Maintenance Upgrade (SMU)      | Yes                 | Yes                  |
| Cisco StackWise Virtual                 | Yes                 | No <sup>2</sup>      |
| Stateful Switchover (SSO)               | Yes (2 SUP, SVL)    | Yes (2 SUP)          |
| In-Service Software Upgrade (ISSU)      | Yes (2 SUP, SVL)    | Yes (2 SUP)          |
| Graceful Insertion and Removal (GIR)    | Yes                 | Yes                  |
| MKA High Availability                   | Yes                 | Yes <sup>1</sup>     |
| <b>Enterprise Security</b>              |                     |                      |
| Trustworthy Solutions                   | Yes                 | Yes                  |
| Image Signing                           | Yes                 | Yes                  |
| Secure Boot                             | Yes                 | Yes                  |
| Cisco Trust Anchor Module               | Yes                 | Yes                  |
| MACsec Encryption (256-bit AES-GCM)     | Yes                 | Yes                  |
| Cisco WAN MACsec (256-bit AES-GCM)      | No                  | Yes                  |
| Object-Group ACLs (IPv4/IPv6)           | Yes                 | Yes                  |
| <b>Enterprise QoS</b>                   |                     |                      |
| Modular QoS CLI (MQC)                   | Yes                 | Yes                  |
| Strict Priority Queuing                 | Yes                 | Yes                  |
| Class/Color-aware Queuing               | Yes (WFQ)           | Yes (VoQ)            |
| Policing/Metering                       | Yes                 | Yes                  |
| Shaping/Bandwidth                       | Yes                 | Yes                  |
| Hierarchical QoS                        | Yes (2-level)       | Yes (2-level)        |

| Model   | Catalyst 9600 SUP-1 | Catalyst 9600X SUP-2 |
|---|---------------------|----------------------|
| <b>IP Routing</b>   |                     |                      |
| Routing Information Protocol version 2 (RIPv2), and next generation (RIPng) | Yes                 | Yes                  |
| Open Shortest Path First version 2 (OSPFv2), and OSPFv3                     | Yes                 | Yes                  |
| Enhanced Interior Gateway Routing Protocol (EIGRP), and EIGRPv6             | Yes                 | Yes                  |
| Intermediate System-to-Intermediate System Version 4 (IS-ISv4)              | Yes                 | Yes                  |
| Border Gateway Protocol version 4 (BGPv4), and BGPv6                        | Yes                 | Yes                  |
| Protocol-Independent Multicast (PIM) Sparse-Mode (PIM-SM)                   | Yes                 | Yes                  |
| Protocol-Independent Multicast (PIM) Source-Specific Mode (PIM-SSM)         | Yes                 | Yes                  |
| Bidirectional PIM (BIDIR-PIM)   | Yes                 | No                   |
| Model   | Catalyst 9600       | Catalyst 9600X       |
| IPv6 routing  | Yes                 | Yes                  |
| L3 Routed Sub-Interfaces  | Yes                 | Yes                  |
| <b>Multi-Protocol Label Switching (MPLS)</b>                                |                     |                      |
| MPLS L3 VPN   | Yes                 | Yes                  |
| Ethernet over MPLS (EoMPLS)   | Yes                 | Yes                  |
| Virtual Private LAN Service (VPLS)  | Yes                 | No <sup>2</sup>      |
| MPLS over GRE   | Yes                 | No <sup>2</sup>      |
| MPLS Traffic-Engineering (MPLS-TE)  | Yes                 | Yes <sup>1</sup>     |

| Model                                      | Catalyst 9600 SUP-1 | Catalyst 9600X SUP-2        |
|--|---------------------|-----------------------------|
| <b>Ethernet VPN (EVPN)</b>                 |                     |                             |
| Virtual eXtensible LAN (VXLAN)             | Yes                 | No <sup>2</sup>             |
| L2 Virtual Network Interface (VNI)         | Yes                 | No <sup>2</sup>             |
| L3 Virtual Network Interface (VNI)         | Yes                 | No <sup>2</sup>             |
| Distributed Anycast Gateway                | Yes                 | No <sup>2</sup>             |
| EVPN Spine                                 | Yes                 | No <sup>2</sup>             |
| VPN Border                                 | Yes                 | No <sup>2</sup>             |
| EVPN Leaf                                  | Yes                 | No <sup>2</sup>             |
| <b>Software-Defined Access (SD-Access)</b> |                     |                             |
| Virtual eXtensible LAN (VXLAN)             | Yes                 | Yes                         |
| L2 Virtual Network Interface (VNI)         | Yes                 | Yes                         |
| L3 Virtual Network Interface (VNI)         | Yes                 | Yes                         |
| Distributed Anycast Gateway                | Yes                 | Yes                         |
| SDA Control-Plane                          | Yes                 | Yes                         |
| SDA Border                                 | Yes                 | Yes                         |
| SDA Edge                                   | Yes                 | No                          |
| <b>Flexible NetFlow (FNF)</b>              |                     |                             |
| FNF IPv4 flow records                      | Yes                 | Yes <sup>1</sup> (software) |
| FNF IPv6 flow records                      | Yes                 | Yes <sup>1</sup> (software) |
| FNF sampler                                | Yes                 | Yes <sup>1</sup>            |
| FNF data export                            | Yes                 | Yes <sup>1</sup>            |
| NetFlow version 9 (NFv9) export            | Yes                 | Yes <sup>1</sup>            |
| IPFIX export                               | Yes                 | Yes <sup>1</sup>            |



| Model                   | Catalyst 9600 SUP-1 | Catalyst 9600X SUP-2 |
|-------------------------|---------------------|----------------------|
| <b>Programmability</b>  |                     |                      |
| NETCONF                 | Yes                 | Yes                  |
| RESTCONF                | Yes                 | Yes                  |
| gNMI/gNOI               | Yes                 | Yes                  |
| YANG models             | Yes                 | Yes                  |
| ZTP/PTP                 | Yes                 | Yes                  |
| <b>Smart Operations</b> |                     |                      |
| Bluetooth Wireless UI   | Yes                 | Yes                  |
| RFID tags               | Yes                 | Yes                  |
| Blue beacon             | Yes                 | Yes                  |
| Out-of-Band Management  | Yes                 | Yes                  |

<sup>1</sup> C9600X models: minimum IOSXE software release 17.8.1

<sup>2</sup> C9600X models: feature is not available at FCS, but will be available in future software releases

## Licensing

### Introduction to Smart Licensing

Cisco Smart Licensing is a flexible licensing model that provides you with an easier, faster, and more consistent way to purchase and manage software across the Cisco portfolio and across your organization. And it's secure – you control what users can access. With Smart Licensing you get:

- **Easy Activation:** Smart Licensing establishes a pool of software licenses that can be used across the entire organization—no more PAKs (Product Activation Keys).
- **Unified Management:** My Cisco Entitlements (MCE) provides a complete view into all of your Cisco products and services in an easy-to-use portal, so you always know what you have and what you are using.
- **License Flexibility:** Your software is not node-locked to your hardware, so you can easily use and transfer licenses as needed.
- To use Smart Licensing, you must first set up a Smart Account on Cisco Software Central ([software.cisco.com](https://software.cisco.com)).

For a more detailed overview on Cisco Licensing, go to [cisco.com/go/licensingguide](https://cisco.com/go/licensingguide)

---

## Software Offers

### Software policy for Cisco Catalyst 9600 Series Switches Packaging: Network and Cisco DNA Licensing

The Cisco Catalyst 9000 family of switches introduces a new and simplified licensing package in the form of base and add-on licenses.

- **The base licensing** package includes Network Advantage licensing options that are tied to the hardware. The base licensing packages cover switching fundamentals, management automation, troubleshooting, and advanced switching features. These base licenses are perpetual.
- **The add-on licensing** package includes the Cisco DNA Advantage option. In addition to on-box capabilities, the features available with this package provide Cisco innovations on the switch, as well as on Cisco DNA Center. The Cisco DNA add-on licenses are available as a subscription.

**License consumption** is easily determined by the package itself. While base licenses are always permanent and without an expiration date, add-on licenses have to be purchased for a 3, 5, or 7 year term (and hence are also known as term-based licenses).

### Cisco DNA Advantage Subscription

Cisco DNA Advantage subscriptions offer a flexible way to buy software for the access domain. At each stage in the product lifecycle, Cisco DNA Advantage subscriptions help make buying, managing, and upgrading your network and infrastructure software easier. Cisco DNA Advantage subscriptions provide:

- Flexible licensing models to smoothly distribute customers' software spending over time
- Investment protection for software purchases through software services-enabled license portability
- Lower cost of entry with the new Cisco DNA Advantage Subscription for Switching model

Cisco Catalyst 9600 Series Supervisor 1 based switches run on Cisco IOS XE Release 16.11.1 or later. Catalyst 9600 Series Supervisor 2 based switches run on Cisco IOS XE Release 17.7.1 or later. This software release includes all the features listed earlier in the Platform Software Benefits section.

**Managing Licenses with Smart Accounts:** Creating Smart Accounts by using the Cisco Smart Software Manager (Cisco SSM) enables you to order devices and licensing packages and also manage your software licenses from a centralized website. You can set up Cisco SSM to receive daily email alerts and to be notified of expiring add-on licenses that you want to renew.

You must order an add-on license in order to purchase a switch. When the license term expires, you can either renew the add-on license to continue using it or deactivate the add-on license and then reload the switch to continue operating with the base license capabilities.

Both the base and add-on licenses are also available for a 90-day evaluation period. An evaluation license is activated temporarily, without purchase. An expired evaluation license cannot be reactivated after reload.

**Note:** It is not required to deploy Cisco DNA Center, just to use one of the above packages.

## Software Policy for Cisco Catalyst 9600 Series Switches

Cisco DNA Software for Access Switching is available for the Cisco Catalyst 9600 Series. Cisco DNA Software for Access Switching offers comprehensive solutions for the enterprise campus and branch offices. Cisco ONE for Access Switching introduces a simpler and more economical way to deploy access, aggregation, and core switches across enterprise campus and branch locations.

The Cisco DNA Subscription for Switching offer delivers an unbound network on an open and extensible architecture to help you navigate the digital journey. This subscription offer simplifies the buying process and includes lower initiation costs and flexible terms. It includes Cisco DNA Advantage with full Cisco Digital Network Architecture (Cisco DNA) capabilities and Cisco SD-Access.

For ordering information for Cisco DNA Software for the Cisco Catalyst 9600 Series, go to <https://www.cisco.com/c/en/us/products/software/one-access/switching-part-numbers.html>.

### Software Policy for Network Stack components

Customers with the Network Essential Stack and Network Advantage Stack software feature sets will be provided with maintenance updates and bug fixes. These are designed to maintain compliance of the software with published specifications, release notes, and industry standards as long as the original end user continues to own or use the product or for up to one year from the end-of-sale date for the product, whichever occurs earlier.

### Cisco Embedded Support for Cisco DNA Term Components

Cisco Embedded Support delivers the right support for Cisco software products and suites. It will keep your business applications performing as expected and protect your investment. Cisco Embedded Support for the Cisco DNA Essentials and Cisco DNA Advantage term components is included as part of the switch value. Embedded Support provides access to TAC support, major software updates, maintenance and minor software releases, and the Cisco Software Support site, for increased productivity with anytime access.

## Network Licensing

**Table 2.** Network advantage package features

| Features on Cisco Catalyst uplink switches  | Network Advantage |
|---|-------------------|
| <b>Switch Fundamentals</b><br>Layer 2, Routed Access (RIP, EIGRP Stub, OSPF), PBR, PIM Stub Multicast, PVLAN, VRRP, PBR, Cisco Discovery Protocol, QoS, FHS, 802.1X, CoPP, SXP, IP SLA Responder, SSO | ✓                 |
| <b>Advanced Switch Capabilities and Scale</b><br>BGP, EIGRP, HSRP, IS-IS, BSR, MSDP, PIM SM, PIM SSM, BIDIR-PIM, IP SLA, OSPF   | ✓                 |
| <b>Network Segmentation</b><br>VRF, Software-Defined Access (VXLAN, LISP, SGT), MPLS, mVPN*   | ✓                 |
| <b>Automation</b><br>NETCONF, RESTCONF, gRPC, YANG, PnP Agent, ZTP/Open PnP, GuestShell (on-box Python)   | ✓                 |

| Features on Cisco Catalyst uplink switches   | Network Advantage |
|--|-------------------|
| <b>Telemetry and Visibility</b><br>Model-driven telemetry, sampled NetFlow, SPAN, RSPAN* | ✓                 |
| <b>Security</b><br>MACsec-256  | ✓                 |

\*Sup-2: FCS+

## Cisco DNA Licensing

**Table 3.** Cisco DNA Advantage package features

| Features   | Cisco DNA Advantage |
|--|---------------------|
| <b>Switch Features</b>   |                     |
| <b>Advanced telemetry and visibility</b><br>Full Flexible NetFlow, EEM   | ✓                   |
| <b>Cisco DNA Center Features</b>   |                     |
| <b>Day-0 network bring-up automation</b><br>Cisco Network Plug-and-Play application, network settings, device credentials, LAN automation, host onboarding | ✓                   |
| <b>Element Management</b><br>Discovery, inventory, topology, software image, licensing, and configuration management                                       | ✓                   |
| <b>Element Management</b><br>Patch management  | ✓                   |
| <b>Basic Assurance</b><br>Health dashboards - Network, Client, Application; switch and wired client health monitoring                                      | ✓                   |
| <b>SD-Access</b><br>Policy-based automation and assurance for wired and wireless   | ✓                   |

For a full list of features, please see the Cisco DNA Software for Switching feature matrix:

[https://www.cisco.com/c/m/en\\_us/products/software/dna-subscription-switching/en-sw-sub-matrix-switching.html?OID=otren019471](https://www.cisco.com/c/m/en_us/products/software/dna-subscription-switching/en-sw-sub-matrix-switching.html?OID=otren019471)

## Cisco IOS XE

- This modern operating system for the enterprise provides support for model-driven programmability, on-box Python scripting, streaming telemetry, container-based application hosting, and patching for critical bug fixes. Cisco IOS® XE also has built-in defenses to protect against runtime attacks.
- Plug and Play enabled: A simple, secure, unified, and integrated offering eases new branch or campus device rollouts and can also be used to provide updates to an existing network.
- **Advanced Security**
  - Advanced Encryption Standard 256 (AES-256) support with the powerful MACsec-256 encryption algorithm is available in hardware.
  - Trustworthy solutions: Secure Unique Device Identification (SUDI) support for Plug and Play (PnP) tamper-proof device identity capability secures zero-touch provisioning by allowing your device to show a certificate to the server to be able to get on your network.

## SD-Access

- SD-Access is Cisco's leading enterprise architecture. It includes:
  - Policy-based automation from edge to cloud
  - Macro-segmentation and micro-segmentation made easy, with predictable performance and scalability
  - Automation through the Cisco DNA Center Appliance
  - Policy through the Cisco Identity Services Engine (ISE)
  - Network assurance through the Network Data Platform

## Cisco Catalyst 9600 Series Chassis

Cisco Catalyst 9600 Series switches offers one chassis option and multiple line-card options (Table 1). It provides a common architecture that can scale up to 192 10 Gigabit or 25 Gigabit Ethernet ports. The Cisco Catalyst 9600 Series redundant chassis offer High Availability (HA) by supporting 1 + 1 redundant supervisor engines with full-image In-Service Software Upgrades (ISSU). NSF/SSO and ISSU help ensure continuous packet forwarding during supervisor engine switchover to enable HA for business-critical applications.

The Cisco Catalyst 9600 Series chassis is enterprise optimized, with efficient side-to-side airflow and full front accessibility for all removable components, including supervisors, line cards, power supplies, and fan tray. The chassis also supports optional rear accessibility for the fan tray to enable efficient cable management. The Cisco Catalyst 9600 Series chassis, supervisor, line cards, power supply, and fan tray have embedded RFID tags that facilitate easy asset and inventory management using commercial RFID readers.

**Table 4.** Chassis Features

| Feature                 | Cisco Catalyst 9606R chassis |
|-------------------------|------------------------------|
| Total number of slots   | 6                            |
| Line Card slots         | 4                            |
| Supervisor Engine slots | 2                            |

| Feature  | Cisco Catalyst 9606R chassis                            |
|--|---|
| Dedicated Supervisor Engine slot numbers         | 3 and 4   |
| Supervisor Engine Redundancy                     | Yes   |
| Supervisor Engines Supported                     | C9600-SUP-1, C9600X-SUP-2                               |
| Maximum bandwidth scalability per Line Card slot | 6.4 Tbps With C9600X-SUP-2<br>2.4 Tbps With C9600-SUP-1 |
| Number of Power Supply bays                      | 4   |
| Minimum number of Power Supplies                 | 2 <sup>1</sup>  |
| Power Supplies supported                         | 2000W AC, 2000W DC                                      |
| Number of Fan-tray bays                          | 1   |

<sup>1</sup>Fully loaded C9606R chassis, Minimum 3 power supplies required if input voltage is 110V

## Supervisor configuration

Cisco Catalyst 9600 Series switches offers an industry-leading supervisor engine built for secure networks, IoT applications, next-generation mobility, and cloud adoption. Supervisor Engine 1 is built with the latest UADP ASIC, with its programmable pipeline and template-based, configurable allocation of Layer 2, Layer 3, forwarding, ACLs and QoS entries, making it ready for next-generation technologies.

Table 5 lists the maximum bandwidth per slot.

**Table 5.** Supervisor Engine 1 maximum bandwidth per slot

| Feature                       | Cisco Catalyst 9600 Series Supervisor Engine 1 | Cisco Catalyst 9600X Series Supervisor Engine 2 |
|-------------------------------|--|---|
| Cisco Catalyst C9606R Chassis | 2.4 Tbps per slot                              | 6.4 Tbps per slot                               |

Table 6 lists the minimum software requirements for the Cisco Catalyst 9600 Series Supervisor Engine 1.

**Table 6.** Supervisor Engine 1 minimum software requirements

| Chassis     | Supervisor Engine                               | Minimum Software Requirement                      |
|-------------|---|---|
| Cisco 9606R | Cisco Catalyst 9600 Series Supervisor Engine 1  | Cisco IOS XE Software Release 16.11.1 Cisco 9606R |
|             | Cisco Catalyst 9600X Series Supervisor Engine 2 | Cisco IOS XE Software Release 17.7.1              |

## Line Card Configuration Options

Cisco Catalyst 9600 Series switches offers the ability to mix and match a range of line cards to support numerous cores and aggregation deployments. Supported line cards are listed in Table 7 and 8 by part number.

**Table 7.** Line Cards compatible with Catalyst 9600 Supervisor Engine 1

| Product Number          | Description  | Minimum Software Requirement          |
|-------------------------|--|---------------------------------------|
| <b>C9600-LC-24C</b>     | Cisco Catalyst 9600 Series 24-port 40GE/12-Port 100GE  | Cisco IOS XE Software Release 16.11.1 |
| <b>C9600-LC-48YL</b>    | Cisco Catalyst 9600 Series 48-port 25GE/10GE/1GE   | Cisco IOS XE Software Release 16.11.1 |
| <b>C9600-LC-48TX</b>    | Cisco Catalyst 9600 Series 48-port RJ45 Copper - 10GE/5GE/2.5GE/1GE/100Mbps/10Mbps                                     | Cisco IOX XE Software Release 17.1.1  |
| <b>C9600-LC-48S</b>     | Cisco Catalyst 9600 Series 48-Port 1GE   | Cisco IOX XE Software Release 17.2.1  |
| <b>C9600-LC-40YL4CD</b> | C9600-LC-40YL4CD Cisco Catalyst 9600 Series Combo Linecard<br>40 ports 1/10/25GE SFP and 2 ports 40/100GE QSFP Uplinks | Cisco IOX XE Software Release 17.7.1  |

\*Supported from IOX XE 16.12.2

**Table 8.** Line Cards compatible with Catalyst 9600 Supervisor Engine 2

| Product Number                               | Description   | Minimum Software Requirement         |
|--|---|--------------------------------------|
| <b>Cisco Catalyst 9600 Series Line Cards</b> |   |                                      |
| <b>C9600-LC-24C</b>                          | Cisco Catalyst 9600 Series 24-port 40GE/12-Port 100GE   | Cisco IOS XE Software Release 17.7.1 |
| <b>C9600-LC-48YL</b>                         | Cisco Catalyst 9600 Series 48-port 25GE/10GE  | Cisco IOS XE Software Release 17.7.1 |
| <b>C9600-LC-48TX</b>                         | Cisco Catalyst 9600 Series 48-port RJ45 Copper - 10GE   | Cisco IOX XE Software Release 17.7.1 |
| <b>C9600-LC-40YL4CD</b>                      | Cisco Catalyst 9600 Series Combo Linecard<br>40 ports 10/25/50GE SFP<br>2 ports 40/100/200GE QSFP56 uplinks<br>2 ports 40/100/200/400GE QSFP DD uplinks | Cisco IOX XE Software Release 17.7.1 |
| <b>C9600X-LC-32CD</b>                        | Cisco Catalyst 9600 Series Combo Linecard<br>30 ports 100/40G QSFP28<br>2 ports 400/200/100G QSFP-DD  | Cisco IOS XE Software Release 17.9.1 |

Cisco Catalyst 9600 Series switches has flexible interface types and port densities that allow you to mix and match network configurations to meet the specific needs of campus networks (Table 9).

**Table 9.** Maximum Chassis Port Densities

| Cisco Catalyst 9606R Chassis | C9600-SUP-1 | C9600X-SUP-2     |
|------------------------------|-------------|------------------|
| 400G                         | -           | 8                |
| 200G                         | -           | 8                |
| 100G                         | 48          | 96 <sup>1</sup>  |
| 50G                          | -           | 256 <sup>1</sup> |
| 40G                          | 96          | 96 <sup>1</sup>  |
| 25G                          | 192         | 256 <sup>1</sup> |
| 10G                          | 192         | 256 <sup>1</sup> |
| 5G**                         | 192         | -                |
| 2.5G**                       | 192         | -                |
| 1G                           | 192         | -                |
| 100M**                       | 192         | -                |
| 10M**                        | 192         | -                |

\*\*Using C9600-LC-48TX

<sup>1</sup>With Breakouts

## Physical specifications

Table 10 lists physical specifications of the Cisco Catalyst 9606 chassis.

**Table 10.** Physical specifications of Cisco Catalyst 9606 chassis

| Description  | Specifications                                      |
|--|---|
| SKU  | C9606R  |
| Dimensions (H x W x D)                                 | 35.43 x 44.2 x 40.9 cm<br>13.95 x 17.4 x 16.1 in.   |
| Rack Units (RU)  | 8   |
| Chassis Weight with 2 Power Supplies (AC) and Fan tray | 31.31 kg (69.03 lb)                                 |
| Input Voltage  | AC: 90V to 264V, 47 to 63 Hz AC<br>DC: -40V to -72V |



| Description  | Specifications   |
|--|--|
| Operating Temperature  | -5° to 45° C (23° to 113° F) up to 6000 feet<br>-5° to 40° C (23° to 104° F) up to 10,000 feet               |
| Storage Temperature  | -40° to 75° C (40° to 167° F)  |
| Relative Humidity, Operating and Non-operating, Non-condensing | 10% to 95%, Non-condensing   |
| Altitude   | -60 to 3000 m (-197 to 9843 feet)  |
| Mean Time Between Failures (MTBF) (hours)                      | C9606R chassis: 4,113,900<br>C9606 fan tray: 452,570<br>C9600-PWR-2KWAC: 300,000<br>C9600-PWR-2KWDC: 300,000 |
| Chassis Weight (without Fan tray, without PSU)                 | 25.36 kg<br>(55.90 lb)   |
| Weight of Fan-tray   | 3.56 kg<br>(7.85 lb)   |
| Weight of individual PSUs                                      | AC PSU: 1.2 kg (2.65 lb)<br>DC PSU: 1.28 kg (2.82 lb)  |

## Power supply

The Cisco Catalyst 9600 Series power supplies support two modes of operation.

### Combined Mode

In combined mode, the power available for the entire chassis is equal to the sum of the output power of all of the power supplies multiplied by the share ratio. Additional power supply units operate at ~90% capacity. In combined mode, the power supplies need to be of equal wattage. The power supplies can be AC and DC mixed provided AC input voltage is 220V. Table 10 shows the power output for one, two, three, and four PSUs.

P = Power output of one PSU

Total combined mode power =  $P + (N-1) * P * (\text{share ratio})$

N = 1, 2, 3, or 4

**Table 11.** Power output in combined mode

| Input Voltage | 1 PSU | 2 PSUs | 3 PSUs | 4 PSUs |
|---------------|-------|--------|--------|--------|
| 110V          | 1050W | 2040W  | 3030W  | 4020W  |
| 220V          | 2000W | 3940W  | 5880W  | 7820W  |

## Redundant N+1 Mode

The Cisco Catalyst 9600 Series chassis also supports N+1 redundancy, with N independent input circuits and safeguards against the failure of one (+1) of the circuits during a PSU failure. Additional PSUs operate at ~90% capacity. In redundant mode, the power supplies need to be of equal wattage. The power supplies can be AC and DC mixed provided AC input voltage is 220V. Table 10 shows the power output with two, three, and four PSUs.

**Table 12.** Power Output in N+1 Mode

| Input Voltage | 2 PSUs | 3 PSUs | 4 PSUs |
|---------------|--------|--------|--------|
| 110V          | 1050W  | 2040W  | 3030W  |
| 220V          | 2000W  | 3940W  | 5880W  |

Table 13 gives the power supply specifications for Cisco Catalyst 9600 Series switches. Table 12 shows the BTU output.

**Table 13.** Power Supply Specifications

| Power Supply Feature              | C9600-PWR-2KWAC   | C9600-PWR-2KWDC   |
|-----------------------------------|---|---|
| Max power rating                  | 2000W   | 2000W   |
| Input voltage range and frequency | 90VAC to 140VAC and 180VAC to 264VAC 47 to 63 Hz              | -40VDC to -72VDC frequency  |
| Power supply efficiency           | 94% (typical)   | 92% (typical)   |
| Input current                     | AC 10.5A max at 115VAC (1050W)<br>7.8 A max at 230VAC (2000W) | Maximum: 60A per DC input at -40VDC input (when full PSU loading) |
| Output ratings                    | 12Vmain at 167A   | 12Vmain at 167A   |
| Output holdup time                | AC = 20 ms minimum for system                                 | AC = 5 ms minimum for system                                      |
| Power-supply input receptacles    | AC IEC 60320 C16  | Amphenol C10-638976-000   |
| Power cord rating                 | AC 15A  | DC 70A  |

**Table 14.** BTU details for 9606R chassis with Fan tray

| Total output BTU   | BTU        |
|--------------------|------------|
| C9606R + C9606-FAN | 1621 (max) |

The power listed in Table 12 is the absolute maximum. Typically, the power would be 70% of absolute maximum

**Table 15.** Cisco Catalyst 9600 Series Power Cord Options

| <b>C9600-PWR-2KWAC</b> |  |
|------------------------|--|
| <b>CAB-TA-CN</b>       | China AC Type A Power Cable                                |
| <b>CAB-TA-IS</b>       | Israel AC Type A Power Cable                               |
| <b>CAB-TA-AP</b>       | Australia AC Type A Power Cable                            |
| <b>CAB-TA-AR</b>       | Argentina AC Type A Power Cable                            |
| <b>CAB-TA-DN</b>       | Denmark AC Type A Power Cable                              |
| <b>CAB-TA-EU</b>       | Europe AC Type A Power Cable                               |
| <b>CAB-TA-IN</b>       | India AC Type A Power Cable                                |
| <b>CAB-TA-IT</b>       | Italy AC Type A Power Cable                                |
| <b>CAB-TA-SW</b>       | Switzerland AC Type A Power Cable                          |
| <b>CAB-TA-UK</b>       | United Kingdom AC Type A Power Cable                       |
| <b>CAB-TA-NA</b>       | North America AC Type A Power Cable                        |
| <b>CAB-C15-CBN</b>     | Cabinet Jumper Power Cord, 250 VAC 13A, C14-C15 Connectors |
| <b>CAB-TA-JP</b>       | Japan AC Type A Power Cable                                |
| <b>CAB-C15-CBN-JP</b>  | Japan Cabinet Jumper Power Cord, 250 VAC 12A, C14-C15      |
| <b>CAB-TA-250V-JP</b>  | Japan 250V AC Type A Power Cable                           |
| <b>CAB-ACBZ-12A</b>    | AC Power Cord (Brazil) 12A/125V BR-3-20 plug up to 12A     |
| <b>PWR-2KW-DC-CBL</b>  | Power Cord - 2KW DC  |

## Fan tray

Each Cisco Catalyst 9600 Series switches uses a single serviceable fan tray for cooling. The switches can optionally be accessed from the rear for flexible cable management. The chassis is optimized for enterprise closets, with side-to-side airflow. All fan trays are composed of multiple independently controlled fans. If any single fan fails, the system will continue to operate without a significant degradation in cooling. Fan speeds change dynamically to compensate for fan failure. Cisco Catalyst 9600 Series fans have a barometric sensor, which allows slower fan speed curves at lower altitudes. The fans also have individual Pulse-Wide Modulation (PWM) fine-tuning to reduce variability in fan revolutions per minute (rpm) under throttled conditions. The measured acoustic noise in a formal NEBS test environment is 77.7 Lwad (dB). The chassis are designed to accommodate fanless operation of up to 90 seconds to enable serviceability.



**Figure 2.**  
Cisco Catalyst 9606R Chassis with Fan Tray

## Regulatory standards compliance

Table 16 lists the regulatory standards compliance for Cisco Catalyst 9600 Series switches.

**Table 16.** Safety and Compliance Information (TBD)

| Description                  | Specification  |
|------------------------------|--|
| <b>Safety certifications</b> | <p>C9606R</p> <ul style="list-style-type: none"><li>• IEC 60950-1 plus Am1, Am2, Am9, Am10, Am11, Am12 and all deviations and differences</li><li>• AS/NZS 60950.1.2011</li><li>• CAN/CSA-C22.2 No. 60950-1-07</li><li>• GB 4943-95</li><li>• EN 60950-1; 2006 plus Am1, Am 2, Am9, Am10, Am11, Am12 and all deviations and differences</li><li>• NOM-019-SCFI-1998</li><li>• UL 60950-1, Second Edition</li></ul> |

| Description                   | Specification  |
|-------------------------------|--|
| <b>EMI and EMC Compliance</b> | 47 CFR Part 15 Class A<br>CNS13438: 2006 Class A<br>EN 300 386 V1.6.1<br>EN61000-3-2: 2014<br>EN61000-3-3: 2013<br>ICES-003 Issue 6: 2016 Class A<br>KN 32: 2015 Class A<br>TCVN 7189: 2009 Class A<br>EN 55032:2012/ AC:2013 Class A<br>EN 55032:2015 Class A<br>CISPR 32 Edition 2 Class A<br>V-2/2015.04 Class A<br>V-3/2015.04 Class A<br>CISPR24: 2010 + A1: 2015<br>EN 300 386 V1.6.1<br>EN55024: 2010 + A1: 2015<br>KN35: 2015<br>TCVN 7317: 2003 |

## Ordering information

Table 17 lists the ordering information for chassis, power supplies, supervisor engines, and memory that are commonly used with the Cisco Catalyst 9600 Series, as well as the Cisco DNA term licenses.

**Table 17.** Ordering Information

| Product Number           | Description  |
|--------------------------|--|
| <b>C9606R (=)</b>        | Cisco Catalyst 9600 Series 6 Slot Chassis  |
| <b>C9600-SUP-1 (=)</b>   | Cisco Catalyst 9600 Series Supervisor 1 Module                                     |
| <b>C9600-SUP-1/2</b>     | Cisco Catalyst 9600 Series Redundant Supervisor 1 Module                           |
| <b>C9600X-SUP-2</b>      | Cisco Catalyst 9600 Series Supervisor 2 Module                                     |
| <b>C9600X-SUP-2/2</b>    | Cisco Catalyst 9600 Series Redundant Supervisor 2 Module                           |
| <b>C9600-LC-24C (=)</b>  | Cisco Catalyst 9600 Series 24-Port 40GE/12-Port 100GE                              |
| <b>C9600-LC-48YL (=)</b> | Cisco Catalyst 9600 Series 48-Port 25GE/10GE/1GE                                   |
| <b>C9600-LC-48TX (=)</b> | Cisco Catalyst 9600 Series 48-port RJ45 Copper - 10GE/5GE/2.5GE/1GE/100Mbps/10Mbps |

| Product Number              | Description   |
|-----------------------------|---|
| <b>C9600-LC-48S (=)</b>     | Cisco Catalyst 9600 Series 48-Port 1GE  |
| <b>C9600-LC-40YL4CD (=)</b> | Cisco Catalyst 9600 Series Combo Linecard<br>40 ports 10/25/50GE SFP<br>2 ports 40/100/200GE QSFP56 uplinks<br>2 ports 40/100/200/400GE QSFP DD uplinks |
| <b>C9600X-LC-32CD (=)</b>   | Cisco Catalyst 9600 Series Combo Linecard<br>30 ports 100/40G QSFP28<br>2 ports 400/200/100G QSFP-DD  |
| <b>C9606-FAN (=)</b>        | Cisco Catalyst 9600 Series C9606 Chassis Fan Tray   |
| <b>C9K-F2-SSD-240GB (=)</b> | Cisco Catalyst 9600 Series 240GB SSD Storage  |
| <b>C9K-F2-SSD-480GB (=)</b> | Cisco Catalyst 9600 Series 480GB SSD Storage  |
| <b>C9K-F2-SSD-960GB (=)</b> | Cisco Catalyst 9600 Series 960GB SSD Storage  |
| Cisco DNA Term Licenses     | Description   |
| <b>C9600-DNA-A</b>          | C9600 Cisco DNA Advantage Term License  |
| <b>C9600-DNA-A-3Y</b>       | C9600 Cisco DNA Advantage 3 Year License  |
| <b>C9600-DNA-A-5Y</b>       | C9600 Cisco DNA Advantage 5 Year License  |
| <b>C9600-DNA-A-7Y</b>       | C9600 Cisco DNA Advantage 7 Year License  |
| Power Supplies              | Description   |
| <b>C9600-PWR-2KWAC (=)</b>  | Cisco Catalyst 9600 Series 2000W AC Power Supply  |
| <b>C9600-PWR-2KWDC (=)</b>  | Cisco Catalyst 9600 Series 2000W DC Power Supply  |
| Spare Accessories and Kits  | Description   |
| <b>C9606-SLOT-BLANK (=)</b> | Cisco Catalyst 9600 Series Blank for Chassis Module Slot  |
| <b>C9606-PWR-BLANK (=)</b>  | Cisco Catalyst 9600 Series Blank for Chassis Power Supply Slot  |
| <b>CAB-CONSOLE-USB</b>      | Console Cable 6ft with USB Type A and mini-B  |
| <b>CAB-CONSOLE-RJ45</b>     | Console Cable 6ft with RJ45 and DB9F  |
| <b>C9606-RACK-KIT=</b>      | Cisco Catalyst 9600 Series 6 slot chassis Rack Mount  |
| <b>C9606-ACC-KIT=</b>       | Cisco Catalyst 9600 Series 6 slot chassis Accessory Kit   |
| <b>C9606-SHELF-KIT=</b>     | Cisco Catalyst 9600 Series 6 slot chassis Shelf Install Kit   |
| <b>C9606-FB-23-KIT=</b>     | Cisco Catalyst 9600 Series 6 slot chassis Front to Back Kit   |

## Pro sustainability

Information about Cisco’s environmental, Social and Governance (ESG) initiatives and performance is provided in Cisco’s CSR and sustainability reporting.

**Table 18.** Product Sustainability

| Sustainability Topic | Reference   |  |
|----------------------|---|--|
| <b>General</b>       | Information on product-material-content laws and regulations  | <a href="#">Materials</a>  |
|                      | Information on electronic waste laws and regulations, including our products, batteries and packaging | <a href="#">WEEE Compliance</a>  |
|                      | Sustainability Inquiries  | Contact: <a href="mailto:csr_inquiries@cisco.com">csr_inquiries@cisco.com</a>                                  |
|                      | Information on product takeback and reuse program   | <a href="#">Cisco Takeback and Reuse Program</a>   |
|                      | Safety and compliance   | <a href="#">Table 16. Safety and compliance information</a>  |
|                      | Mean Time Between Failures - MTBF (hours)   | Table.24 Model Dimensions, Weight, and Mean Time between failures metrics                                      |
| <b>Power</b>         | Default AC power supply   | Platform details   |
|                      | Power supplies  | <a href="#">Table 11: Power output in combined mode</a>  |
|                      |   | <a href="#">Table 11: Power Output in N+1 Mode</a>   |
|                      |   | <a href="#">Table 13: Power Supply Specifications</a>  |
|                      | Fan   | <a href="#">Table 14. Fan tray</a>   |
|                      | Energy Efficient Ethernet   | <a href="#">Smart operation</a>  |
|                      | Product packaging weight and materials  | Contact: <a href="mailto:environment@cisco.com">environment@cisco.com</a>                                      |
| Dimensions           | <a href="#">Table 10: Physical specifications of Cisco Catalyst 9606 chassis</a>                      |  |
| <b>Material</b>      | Weight  | <a href="#">Table 10: Physical specifications of Cisco Catalyst 9606 chassis</a>                               |
|                      | Elimination of wet paint on plastic bezel   | <a href="#">2019 Cisco Corporate Social Responsibility Report</a> , Pg. 19 Stepping up our work on circularity |

## Cisco Enhanced Limited Lifetime Hardware Warranty

Cisco Catalyst 9600 Series switches come with an Enhanced Limited Lifetime Warranty (E-LLW) that includes Next-Business-Day (NBD) delivery of replacement hardware where available and 90 days of 8x5 Cisco Technical Assistance Center (TAC) support. Your formal warranty statement, including the warranty applicable to Cisco software, appears in the information packet that accompanies your Cisco product. We encourage you to carefully review the warranty statement shipped with your specific product before use. Cisco reserves the right to refund the purchase price as its exclusive warranty remedy. For further information about warranty terms, visit <https://www.cisco.com/go/warranty>.

Table 19 provides information about the E-LLW.

**Table 19.** E-LLW Details

|                             | Cisco E-LLW  |
|-----------------------------|--|
| <b>Devices Covered</b>      | Applies to Cisco Catalyst 9600 Series switches.  |
| <b>Warranty Duration</b>    | As long as the original customer owns the product.   |
| <b>End-of-Life Policy</b>   | In the event of discontinuance of product manufacture, Cisco warranty support is limited to 5 years from the announcement of discontinuance.   |
| <b>Hardware Replacement</b> | Cisco or its service center will use commercially reasonable efforts to ship a replacement for NBD delivery, where available. Otherwise, a replacement will be shipped within 10 working days after receipt of the Return Materials Authorization (RMA) request. Actual delivery times might vary depending on customer location.  |
| <b>Effective Date</b>       | Hardware warranty commences from the date of shipment to customer (and in case of resale by a Cisco reseller, not more than 90 days after original shipment by Cisco).   |
| <b>TAC Support</b>          | Cisco will provide during business hours, 8 hours per day, 5 days per week, basic configuration, diagnosis, and troubleshooting of device-level problems for up to a 90-day period from the date of shipment of the originally purchased Cisco Catalyst 9600 Series product. This support does not include solution or network level support beyond the specific device under consideration. |
| <b>Cisco.com access</b>     | Warranty allows guest access only to Cisco.com.  |



## Cisco Services

Successfully deploy, manage, and support Cisco Catalyst 9000 switches with a full life cycle of Cisco Services including implementation, optimization, technical, managed and training services. Our team of experts can help you speed deployment, reduce costs and minimize risk as you introduce new hardware, software and protocols into the network. As your trusted advisor, we help you achieve extraordinary business outcomes, minimize risk and disruption so you can anticipate change and pivot quickly, securely, and confidently.

**Table 20.** Technical Services

| Cisco Technical Services   |
|--|
| <b>Cisco Smart Net Total Care® Service</b> <ul style="list-style-type: none"><li>• Around-the-clock, global access to the Cisco TAC</li><li>• Unrestricted access to the extensive Cisco.com knowledge base and tools</li><li>• NBD, 8x5x4, 24x7x4, and 24x7x2 advance hardware replacement and onsite parts replacement and installation available</li><li>• Ongoing operating system software updates within the licensed feature set<sup>1</sup></li><li>• Proactive diagnostics and real-time alerts on Smart Call Home-enabled devices</li></ul>  |
| <b>Cisco Solution Support Service</b> <ul style="list-style-type: none"><li>• Provides a team of experts who act as primary point of contact to deliver centralized support, including in multivendor network environments</li><li>• Speed is paramount when problems arise, so we deliver on a 30-minute service level objective and prioritize Solution Support cases</li><li>• Expert guidance helps to enhance IT operations with fewer outages and faster problem resolution while maximizing performance and reliability of Catalyst 9600 Series switches</li><li>• We even look beyond identified problems and provide the necessary guidance needed to help you avoid any pitfalls before they can disrupt IT or your business</li></ul> |

<sup>1</sup>Cisco operating system updates include the following: maintenance releases, minor updates, and major updates within the licensed feature set

[Learn more about available services.](#)

## Software Policy for Cisco Catalyst 9600 Series Switches

**[Cisco DNA Software for Access Switching](#) is available for the Cisco Catalyst 9600 Series.**

Cisco DNA Software for Access Switching offers comprehensive solutions for the enterprise campus and branch offices.

The Cisco DNA Subscription for Switching offer delivers an unbound network on an open and extensible architecture to help you navigate the digital journey. This subscription offer simplifies the buying process and includes lower initiation costs and flexible terms. It includes Cisco DNA Advantage with full Cisco Digital Network Architecture (Cisco DNA) capabilities and Cisco SD-Access.

### Software Policy for Network Stack components

Customers with the Network Essential Stack and Network Advantage Stack software feature sets will be provided with maintenance updates and bug fixes. These are designed to maintain compliance of the software with published specifications, release notes, and industry standards as long as the original end user continues to own or use the product or for up to one year from the end-of-sale date for the product, whichever occurs earlier.

---

## Cisco Embedded Support (SWSS) for Cisco DNA Term Components

Cisco Embedded Support (SWSS) delivers the right support for Cisco software products and suites. It will keep your business applications performing as expected and protect your investment. Cisco Embedded Support for the Cisco DNA Essentials and Cisco DNA Advantage term components is included as part of the switch value. Embedded Support provides access to TAC support, major software updates, maintenance and minor software releases, and the Cisco Software Support site, for increased productivity with anytime access.

## Cisco Capital

### Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more](#).

## Document history

| New or Revised Topic                          | Described In          | Date       |
|---|-----------------------|------------|
| Added C9600X-LC-32CD                          | All applicable tables | 6/14/2022  |
| Added C9600X-SUP-2, C9600-LC-40YL4CD sections | All applicable tables | 02/03/2022 |
| Added C9600-LC-48TX sections                  | All applicable tables | 11/25/2019 |
| Original version of C9600 Switches data sheet | Data sheet            | 03/25/2019 |

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)