
illiili cisco

The Next Frontier for Cloud Networking: Cisco Nexus 400G



Cisco Nexus High-Capacity 400G Data Center Networking



Built for the most demanding environments



Built for customer choice and flexibility



Built to last, for maximum investment protection

Cisco Cloudscale

Cisco Nexus® 9316D-GX

- 1RU, 16p 400G QSFP-DD
- 6.4 Tbps bandwidth
- Up to 64p 100G in a compact 1RU form factor

Cisco Nexus 93600CD-GX

- 1RU 28p 100G QSFP-28 with 8p 400G QSFP-DD
- 6.0 Tbps bandwidth
- High performance for AI/ML workloads

Key differentiators:

- Industry-leader in route scale
- Full data and system telemetry capabilities
- Only 400G silicon with SRv6 forwarding at line rate

ACI leaf and spine capability in same switch

Cisco Nexus 3432D-S

- 1RU, 32p 400G with QSFP-DD
- 12.8 Tbps bandwidth
- · High-density spine



Cisco Nexus 3408-S

- 4RU semimodular switch
- 12.8Tbps bandwidth
- Expansion modules of 8-slots for 100G or 400G LEMs
- 8 slots for different up- and down-link configurations
 - 400G OSFP-DD
- 100G QSFP-28


Key differentiators:

- Industry's lowest latency 450ns at 400G
- Lowest power at high switch radix
- Optimized for Leaf and Spine architectures

Backward compatible with 100GE QSFP-28 and 40GE QSFP+1x 400 GbE/100 GbE/40 GbE Breakout 4x 100 GbE/25 GbE/10 GbE or 8x 50GbE;2x 200 GbE or 4x 50GbE

Cisco Nexus 400G use cases

400G: Terabit-scale switching



Benefits



Superior performance



Consistent reliability



High scalability



Architectural flexibility



Superior availability



Backward compatibility



Investment protection

Bandwidth continues to explode. Cisco® Visual Networking Index (VNI) research data indicates the dawning of a 400G era for mass-scale networking in service providers and data centers.



Webscale customer use case

- Enable transition from 50G to 100G servers with proportionally scaled-out fabrics
- Higher radix switches for optimized power consumption



Cisco ACI™ enterprise deployments

- High-performance I/O and 400G fabric for AI/ML compute clusters
- Sophisticated dynamic fabric load-balancing, smart buffers, and flow-level visibility
- 400G in different fabric tiers



Service provider deployments

- 100G/400G fabrics for spaceconstrained environments in service-provider edge locations
- Ready for NFV/5G adoption cycle

400G optics: QSFP-DD	
PID	Distance, media (connector)
QDD-400-CUxM*	3m passive copper cable*
QDD-400G-AOCxxM*	30m active optical cable*
QDD-400G-SR4-BD	100m MMF ribbon (MPO-12)
QDD-400G-DR4-S*	500m SMF ribbon (MPO-12)*
QDD-400G-FR4-S*	2km duplex SMF (LC)*
QDD-400G-LR8-S	10km duplex SMF (LC)
QDD-400G-ZR-S	120km duplex SMF (LC)
QDD-2X100-SR4-S	100m MMF ribbon (MPO-24)
QDD-2X100-PSM4-S	500m SMF ribbon (MPO-24)
QDD-2X100-CWDM4-S	2km dual duplex SMF (CS)
QDD-2X100-LR4-S	10km dual duplex SMF (CS)

^{*} Available at FCS

To help your organization to upgrade to 400G, contact Cisco today at www.cisco.com/go/400G.