



# Cisco Webex Room 55

CNTTSHOP.VN  
CHUYÊN NGHIỆP - THẬT THIỆN

---

# Contents

Cisco Webex Room 55 overview	3
Cisco Webex Room 55 features and benefits	4
Cisco Webex Room 55 prominent features/differentiators	5
Cisco Webex Room 55 registration	5
Product specifications	6
Regulatory compliance	11
Warranty information	12
Cisco environmental sustainability	12
Cisco Services and Support	13
Cisco Capital	13
Call to action	13

CNTTSHOP.VN  
CHUYÊN NGHIỆP - THÂN THIẾN

---

Cisco Webex Room 55 is a powerful, fully integrated collaboration system that brings more intelligence and usability to your small- to medium-sized meeting rooms, whether registered on-premises or to Cisco Webex.

## Cisco Webex Room 55 overview

Cisco Webex™ Room 55 combines an unmatched video and audio experience with a sophisticated, Red Dot–awarded design to create a compelling team collaboration system.

The Room 55, which includes camera, codec, display, speaker system, and microphones integrated in a single device, is optimized for rooms that seat up to seven people. It is an all-in-one, integrated system that’s easy to install, use, deploy, and manage. It’s crafted with high-quality components: professional 4K display for longevity and minimal latency, powerful digital zoom camera for discreet tracking, sophisticated speaker system and amplifier to deliver rich sound, and a light industrial design that combines aluminum and fabric for a sustainable and humanizing effect.

The Cisco Webex Room 55 has the [Cisco Webex Room Kit](#) as its base technology, bringing new capabilities such as speaker tracking, best overview, automatic wake-up, and people count to enable even smarter meetings, smarter presentation capabilities, and smarter room and device integrations. These features and functionalities further remove the barriers to usage and deployment of video in small- to medium-sized meeting rooms. The Room 55 is rich in functionality and experience but is priced and designed to be easily scalable to all of your meeting rooms and spaces, whether registered on-premises or to Cisco Webex.



**Figure 1.**  
Cisco Webex Room 55 in medium room scenario

## Cisco Webex Room 55 features and benefits

Table 1 summarizes Cisco Webex Room 55 features and benefits.

**Table 1.** Features and benefits

Feature	Benefit
<b>Award-winning design</b>	<ul style="list-style-type: none"> <li>● Light, sophisticated industrial design is recipient of 2017 Red Dot award for innovation in design</li> <li>● Camera innovation: Powerful 5K UltraHD camera and wide-angle lens cover everyone in the room</li> <li>● Sound innovation               <ul style="list-style-type: none"> <li>◦ Stereo speakers with dedicated center speaker for optimal voice pick-up</li> <li>◦ Built-in amplifier to deliver rich sound</li> <li>◦ Speakers above screen for more equal room coverage</li> </ul> </li> <li>● Screen innovation: 4K professional-grade screen</li> <li>● Design innovation               <ul style="list-style-type: none"> <li>◦ Fabric front for natural and inviting feel</li> <li>◦ Aluminium frame for lightness in design and sustainability</li> <li>◦ Increased height over previous generation to accommodate taller tables (10 cm/4 inches taller than MX300)</li> </ul> </li> <li>● Highly reliable as components and software are designed to work together</li> <li>● Designed to minimize latency and echo</li> </ul>
<b>Smart meetings</b>	<ul style="list-style-type: none"> <li>● Brings intelligent views to smaller rooms with discreet, integrated camera               <ul style="list-style-type: none"> <li>◦ Best overview: Automatically detects meeting participants and provides ideal framing</li> <li>◦ Speaker tracking: Detects and switches between active speakers and provides ideal framing</li> </ul> </li> <li>● Great audio experience with integrated microphones, speakers, and amplifier; supports room elegance with no wires or microphones on the table</li> <li>● Automatic noise suppression reduces disruptive sounds coming from the meeting room (e.g., typing, paper rustling)</li> <li>● Simplified meeting-join experience with One Button To Push (OBTP) for scheduled devices in a Cisco Webex Meetings or Webex Teams meetings, whether registered on-prem or to Cisco Webex</li> <li>● Automatic wake-up: System “wakes up” when someone walks into the room and suggests activities for fast and easy meeting start</li> <li>● Easily controlled by the Cisco Touch 10 control unit (Touch 10) or with a Cisco Proximity or the Cisco Webex Teams app</li> <li>● End-to-end security</li> </ul>
<b>Smart presentations</b>	<ul style="list-style-type: none"> <li>● Supports dual screens for video and content</li> <li>● Supports dual content sources for local meetings</li> <li>● View white board content and annotations shared from Cisco Webex Board, Cisco Webex DX80, or Cisco Webex Teams app; participate in white boarding sessions through Cisco Webex Teams app*</li> <li>● 4K content sharing (local 30 fps, remote 5 fps)</li> <li>● Wired or wireless content sharing (only two wires required: power and HDMI)</li> </ul>
<b>Smart rooms</b>	<ul style="list-style-type: none"> <li>● Metrics: Counts people in the room, enabling analytics for better resource planning</li> <li>● Supports Wi-Fi</li> <li>● In-room control: Controls peripherals such as lights and blinds through the Touch 10</li> </ul>
<b>Built for cloud and premises</b>	<ul style="list-style-type: none"> <li>● Flexibility to register on-premises or to the cloud through Cisco Webex</li> <li>● Hardware is optimized to run on a cloud platform for great experiences in shared rooms and spaces, with easy access to hosted conferences</li> </ul>

\* Supported on devices registered to Cisco Webex only

## Cisco Webex Room 55 prominent features/differentiators

### Bringing more intelligence to small and medium-sized rooms

The Cisco Webex Room 55 offers video innovation encased in a beautifully designed frame, bringing more sophistication, intelligence, and usability to your small-to-medium team collaboration rooms. While others are still struggling to offer advanced features such as speaker tracking, wireless sharing, and 4K content in their high-end products, Cisco is already bringing these innovations to meeting rooms of all sizes in a cost-effective and simple way. With the Room 55, Cisco is helping customers experience smarter meetings, enable smarter presentations, and create smarter room and device integrations. These features were previously the domain of higher-end video conferencing rooms, but can now be brought to every room and every team. When registered to Cisco Webex, additional functionalities enhance the user experience and team workflow and further simplify deployment:

- **Smart meetings:** Powerful, integrated cameras deliver intelligent view capabilities, such as automatic framing and speaker tracking; automatic noise suppression reduces meeting disruptions
- **Smart presentations:** Dual screens, dual content sources, wireless sharing, and 4K content make for great presentations
- **Smart rooms:** People count for usage metrics and resource allocation; tight integrations with screens to enhance user interactions; APIs and macros allow meeting personalization
- **Registration flexibility:** Built for both cloud and on-premises deployment, protecting your investment.

## Cisco Webex Room 55 registration

Table 2 provides registration information.


















Table 2. Registration information



License level	Term
Cisco Webex Device Subscription	Monthly or 1-, 2-, 3-, 4-, or 5-year options

# Product specifications

Table 3 provides product specifications.

**Table 3.** Specifications

Specification	Description	
<b>Software compatibility</b>	<ul style="list-style-type: none"> <li>• Cisco Collaboration Endpoint Software Version 9.1.1 or later, and Cisco Webex Room OS</li> </ul>	
<b>Default components in Cisco Webex Room 55 with:</b>		
<b>Floor stand</b>		 Touch controller.  Network cable, flat for touch controller. 8m/26.2ft  Bumpers 4x  HDMI cable. 8m/26.2ft  Network cable, round. 5m/16.4ft  Power cable. 5m/16.4ft  2x Mic10 7.5m/24.6ft
<b>Wheel base</b>		 Cable hook.  Wheels. 2x 2x w/brake  Touch controller.  Network cable, flat for touch controller. 8m/26.2ft  HDMI cable. 8m/26.2ft  Network cable, round. 5m/16.4ft  Power cable. 5m/16.4ft  2x Mic10 7.5m/24.6ft

Specification	Description	
Wall mount		
Optional hardware components	<ul style="list-style-type: none"> <li>• Microphone extension cable</li> <li>• HDMI presentation cable 8m/26.2 ft.</li> </ul>	
Bandwidth	<ul style="list-style-type: none"> <li>• Up to 6 Mbps point-to-point</li> </ul>	
Minimum bandwidth for resolution/frame rate	<p>H.264:</p> <ul style="list-style-type: none"> <li>• 720p30 from 768 kbps</li> <li>• 720p60 from 1152 kbps</li> <li>• 1080p30 from 1472 kbps</li> <li>• 1080p60 from 2560 kbps</li> </ul>	
Firewall traversal	<ul style="list-style-type: none"> <li>• Cisco Expressway™ technology</li> <li>• H.460.18, H.460.19 firewall traversal</li> </ul>	
Video standards	<ul style="list-style-type: none"> <li>• H.264</li> <li>• H.265</li> </ul>	
Video inputs	<ul style="list-style-type: none"> <li>• Two HDMI input supports formats up to maximum 4K (3840 x 2160) at 30 fps, including HD1080p60; HDMI 2 supports HDCP content for local viewing</li> <li>• Consumer Electronics Control (CEC) 2.0</li> </ul>	
Video outputs	<ul style="list-style-type: none"> <li>• One HDMI output supports formats up to 3840 x 2160 at 60 fps (4Kp60)</li> <li>• Live video resolutions (encode and decode) up to 1920 x 1080 at 30, 60 fps (HD1080p)</li> <li>• Consumer Electronics Control (CEC) 2.0</li> </ul>	
Audio standards	<ul style="list-style-type: none"> <li>• G.711, G.722, G.722.1, G.729, AAC-LD, and Opus</li> </ul>	
Audio features	<ul style="list-style-type: none"> <li>• High-quality 20-kHz audio</li> <li>• Prepared for inductive loop (line out)</li> <li>• Automatic Gain Control (AGC)</li> <li>• Automatic noise reduction</li> <li>• Active lip synchronization</li> </ul>	

Specification	Description
Audio inputs	<ul style="list-style-type: none"> <li>• Two microphones, 4-pin minijack</li> <li>• Two audio in from HDMI</li> <li>• Internal microphone</li> </ul>
Audio outputs (external)	<ul style="list-style-type: none"> <li>• 1 line out minijack (stereo)</li> </ul>
Speakers (integrated)	<ul style="list-style-type: none"> <li>• High-quality speaker system with left, center, and right channels, plus woofer</li> <li>• Frequency response 70 Hz to 20 kHz</li> <li>• Amplifier power: 80W</li> <li>• Max output level SPL 98 dB</li> </ul>
Speaker tracking	<ul style="list-style-type: none"> <li>• 6-element microphone array for accurate speaker tracking</li> </ul>
Display	<ul style="list-style-type: none"> <li>• 55 in. (1.4m) LCD monitor, LED backlight</li> <li>• Resolution: 3840 x 2160 (16:9)</li> <li>• Contrast ratio: typical 1100</li> <li>• Viewing angle: +/- 178 degrees</li> <li>• Response time: typical 8 ms</li> <li>• Brightness: typical 500 cd/m2</li> </ul>
Dual stream	<ul style="list-style-type: none"> <li>• H.239 (H.323) dual stream</li> <li>• Binary Floor Control Protocol (BFCP) (SIP) dual stream</li> <li>• Supports resolutions up to 3840 x 2160 at 5 fps</li> </ul>
Wireless sharing	<ul style="list-style-type: none"> <li>• Cisco Webex Teams app (up to 3840 x 2160 at 5 fps)</li> <li>• Cisco Intelligent Proximity client (up to 1920 x 1080 at 5 fps)</li> </ul>
Multipoint support	<ul style="list-style-type: none"> <li>• 4-way embedded SIP/H.323 conferencing capability with MultiSite option</li> </ul>
MultiSite features (embedded multipoint) (optional upgrade)	<ul style="list-style-type: none"> <li>• Adaptive SIP/H.323 MultiSite: <ul style="list-style-type: none"> <li>◦ 3-way resolution up to 1080p30 + content up to 4Kp5</li> <li>◦ 4-way resolution up to 720p30 + content up to 4Kp5</li> </ul> </li> <li>• Full individual audio and video transcoding</li> <li>• H.323/SIP/VoIP in the same conference</li> <li>• Support for presentation (H.239/BFCP) from any participant at resolutions up to 3840 x 2160p5</li> <li>• Best impression (automatic continuous presence layouts)</li> <li>• Encryption and dual stream from any site</li> </ul>
Protocols	<ul style="list-style-type: none"> <li>• H.323</li> <li>• SIP</li> <li>• Cisco Webex</li> </ul>



Specification	Description
<b>Embedded encryption</b>	<ul style="list-style-type: none"> <li>• H.323 and SIP point-to-point</li> <li>• Standards-based: H.235 v3 and Advanced Encryption Standard (AES)</li> <li>• Automatic key generation and exchange</li> </ul>
<b>IP network features</b>	<ul style="list-style-type: none"> <li>• DNS lookup for service configuration</li> <li>• Differentiated services (Quality of Service [QoS])</li> <li>• IP-adaptive bandwidth management (including flow control)</li> <li>• Automatic gatekeeper discovery</li> <li>• Dynamic playout and lip-sync buffering</li> <li>• H.245 Dual-Tone Multifrequency (DTMF) tones in H.323</li> <li>• RFC 4733 DTMF tones in SIP</li> <li>• Date and time support using Network Time Protocol (NTP)</li> <li>• Packet loss-based downspeeding</li> <li>• Uniform Resource Identifier (URI) dialing</li> <li>• Dynamic Host Configuration Protocol (DHCP)</li> <li>• 802.1X network authentication</li> <li>• 802.1Q virtual LAN</li> <li>• 802.1p (QoS and Class of Service [CoS])</li> <li>• ClearPath</li> </ul>
<b>Call control</b>	<ul style="list-style-type: none"> <li>• Cisco Unified Communications Manager (CUCM) <ul style="list-style-type: none"> <li>◦ Native registration with CUCM</li> <li>◦ Requires CUCM Version 10.5.2 or later with device pack for Room 55</li> </ul> </li> <li>• Cisco Expressway <ul style="list-style-type: none"> <li>◦ Native registration with Expressway</li> </ul> </li> <li>• Cisco Webex</li> <li>• Third-party H.323 Gatekeepers and standards-based SIP proxies</li> </ul>
<b>IPv6 network support</b>	<ul style="list-style-type: none"> <li>• Single call stack support for both H.323 and SIP</li> <li>• Dual-stack IPv4 and IPv6 for DHCP, SSH, HTTP, HTTPS, DNS, DiffServ</li> <li>• Support for both static and automatic IP configuration (stateless address auto-configuration)</li> </ul>
<b>Security features</b>	<ul style="list-style-type: none"> <li>• Management using HTTPS and SSH</li> <li>• IP administration password</li> <li>• Menu administration password</li> <li>• Disable IP services</li> <li>• Network settings protection</li> </ul>
<b>Certificate management</b>	<ul style="list-style-type: none"> <li>• Certificate Authority Proxy Function (CAPF) support for additional security</li> <li>• Manufacturer-Installed Certificates (MIC)</li> <li>• Locally Significant Certificates (LSC)</li> <li>• X.509 Digital Certificates (DER encoded binary); both DER and Base-64 formats are acceptable for the client and server certificates; certificates with a key size of 1024, 2048, and 4096 are supported</li> </ul>

Specification	Description
Other interfaces	<ul style="list-style-type: none"> <li>• USB 2.0 port type A, USB 2.0 port type B, <math>\mu</math>USB, factory reset pinhole</li> </ul>
Power	<ul style="list-style-type: none"> <li>• Autosensing power supply</li> <li>• 100-240 VAC, 1.8-0.8A, 50/60 Hz</li> <li>• Rated: 142W maximum</li> <li>• Power consumption: 142W at maximum standardized configuration</li> <li>• Standby power consumption: 40W</li> </ul>
Operating temperature and humidity	<ul style="list-style-type: none"> <li>• 0°C to 40°C (32°F to 104°F) ambient temperature</li> <li>• 10% to 90% Relative Humidity (RH)</li> </ul>
Storage and transport temperature	<ul style="list-style-type: none"> <li>• -20°C to 60°C (-4°F to 140°F) at RH 10% to 90% (noncondensing)</li> </ul>
Physical dimensions (H x W x D)	<p>Cisco Webex Room 55 with:</p> <ul style="list-style-type: none"> <li>• Floor stand: 62.7 x 49 x 30.5 in (1593 x 1245 x 774mm)</li> <li>• Wall mount: 32.8 x 49.0 x 5.1 in (832 x 1245 x 130mm)</li> <li>• Wheel base: 62.7 x 49.0 x 30.5 in (1651 x 1245 x 774mm)</li> </ul>
Weight	<p>Cisco Webex Room 55 with (all weight without packaging):</p> <ul style="list-style-type: none"> <li>• Floor stand: 83.8 lb (38kg)</li> <li>• Wall mount: 68.3 lb (31kg)</li> <li>• Wheel base: 85.1 lb (38.6kg)</li> <li>• Main unit only: 66.1 lb (30kg)</li> </ul>
Physical dimensions and weight of packaging (H x W x D)	<p>Cisco Webex Room 55 package size with:</p> <ul style="list-style-type: none"> <li>• Floor stand: 42.5 x 54.3 x 17.3 in (1080 x 1380 x 440mm)</li> <li>• Wall mount: 46.9 x 53.9 x 17.3 in (1190 x 1370 x 440mm)</li> <li>• Wheel base: 42.5 x 54.3 x 17.3 in (1080 x 1380 x 440mm)</li> </ul> <p>Cisco Webex Room 55 shipping weight with:</p> <ul style="list-style-type: none"> <li>• Floor stand: 110 lb (50kg)</li> <li>• Wall mount: 88 lb (40kg)</li> <li>• Wheel base: 110 lb (50kg)</li> </ul>
Camera overview	<ul style="list-style-type: none"> <li>• 5K UltraHD camera</li> <li>• Supports up to 60 fps (max 30 fps with speaker tracking and best overview enabled)</li> <li>• 15.1 MP image sensor (5184 x 2916 pixels)</li> <li>• 1/1.7 CMOS</li> <li>• 3x zoom</li> <li>• f/2.0 aperture</li> <li>• 83° horizontal field of view/51.5° vertical field of view</li> <li>• Auto-framing (audio + face detect)</li> <li>• Autofocus, brightness, and white balance</li> <li>• Focus distance 1m to infinity</li> </ul>

## Regulatory compliance

Directive 2014/35/EU (Low-Voltage Directive)

Directive 2014/30/EU (EMC Directive) – Class A

Directive 2014/53/EU (Radio Equipment Directive)

Directive 2011/65/EU (RoHS)

Directive 2002/96/EC (WEEE)

NRTL approved (Product Safety)

FCC CFR 47 Part 15B (EMC) – Class A

FCC Listed (Radio Equipment)

For approval documents per country, check the Product Approval Status Database at <https://www.ciscofax.com/>.

To place an order, contact your local Cisco representative and refer to Table 4.

**Table 4.** Ordering information

Product name	Part number	Compliance model number
Cisco Webex Room 55: Subscription pricing (MSRP*) Cisco Webex device with encryption Cisco Touch 10 control unit	CS-ROOM55-MSRP-K9 CS-R55-UNIT-K9+ CTS-CTRL-DVX-10+	TTC60-21 TTC5-09
Cisco Webex Room 55: Upfront pricing (GPL **) Cisco Webex device with encryption Cisco Touch 10 control unit	CS-ROOM55-K9 CS-R55-UNIT-K9+ CTS-CTRL-DVX-10+	TTC60-21 TTC5-09
Cisco Webex Room 55: no radio Cisco Webex device no radio Cisco Touch 10 control unit	CS-ROOM55-NR-K9 CS-R55-UNIT-NR-K9+ CTS-CTRL-DVX-10+	TTC60-21 TTC5-09
Cisco Webex Room 55: no radio, no encryption Cisco Webex device no radio and no encryption Cisco Touch 10 control unit	CS-ROOM55-NR-K7 CS-R55-UNIT-NR-K7+ CTS-CTRL-DVX-10+	TTC60-21 TTC5-09
<b>Options</b>		
Presentation cable 8m 4kp30 certified	CAB-PRES-2HDMI-GR	
<b>Spares</b>		
Floor Stand Kit	CS-ROOM55-FSK=	
Wall Mount Kit	CS-ROOM55-WMK=	
Wheel Base Kit	CS-ROOM55-WBK=	

Product name	Part number	Compliance model number
Wheels Upgrade Kit (With cable hook)	CS-ROOM55-WUK=	
Speaker Grille Kit	CS-ROOM55-SGK=	
Spare Rear Cover	CS-ROOM55-RC=	
Spare Touch 10 control Unit	CTS-CTRL-DV10=	
Spare Ethernet cable	CAB-NET-EN5M=	
Spare Microphone	CTS-MIC-TABL20=	
Spare Main Unit (Service purpose only)	CS-R55-UNIT-K9=	
Spare Main Unit Non Radio (Service purpose only)	CS-R55-UNIT-NR-K9=	
Spare Main Unit Non Radio and Non Encryption (Service purpose only)	CS-R55-UNIT-NR-K7=	

\* MSRP = manufacturer's suggested retail price

\*\* GPL = global price list

## Warranty information

Cisco Webex Room 55 has a 90-day limited liability warranty.

## Cisco environmental sustainability

Information about Cisco's environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the "Environment Sustainability" section of Cisco's [Corporate Social Responsibility](#) (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the "Environment Sustainability" section of the CSR Report) are provided in the following table:

Sustainability topic	Reference
Information on product material content laws and regulations	<a href="#">Materials</a>
Information on electronic waste laws and regulations, including products, batteries, and packaging	<a href="#">WEEE compliance</a>

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

---

## Cisco Services and Support

Cisco and our partners provide a broad portfolio of smart, personalized services and support that can help you realize the full business value of your Cisco collaboration investment by increasing business agility and network availability. This portfolio of services accelerates business innovation by harnessing the network as a powerful business platform. For more information about these services, visit <https://www.cisco.com/go/collaborationservices>.


## Cisco Capital

### Flexible payment solutions to help you achieve your objectives.

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more](#).

## Call to action

- Learn more about [Cisco Webex Room 55](#).
- Download the [Cisco Webex Teams app](#).



**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)