# AMPLIFI





**AmpliFi**<sup>™</sup> **Teleport System** 

**Model: AFi-RT** 

**Personal Wi-Fi Hotspot** 

**Home Network Expanded** 

Secure, Encrypted Connectivity

## The Home Wi-Fi that Covers the World

AmpliFi™ Teleport provides a secure and convenient way to access resources at home, even when you are not. Utilizing any Wi-Fi hotspot or wired Ethernet connection, Teleport is able to create an encrypted connection to your home network, expanding it wherever you go.

Teleport works in two parts – an AmpliFi HD Router runs your home network and Wi-Fi while AmpliFi Teleport, which is a portable hardware extension to the router, makes the home network and its internet connection available from a different location.

The AmpliFi HD Router has a dual-band 802.11ac 3x3 MIMO Wi-Fi, multiple self-configuring radios and advanced antenna technology, bringing full Wi-Fi coverage throughout your home.

AmpliFi Teleport is a compact, portable plug-in device that provides both an Ethernet port and Wi-Fi connectivity, either of which can be used to connect to the internet or simply network your devices together.





Teleport and Router Kit Model: AFi-RT



Teleport (Stand-Alone) For Existing AmpliFi Router Users Model: AFi-T







# **Perfected User Experience**

The intuitive AmpliFi app allows instant setup, configuration, powerful reporting metrics, parental controls, remote access, and easy guest access. The mobile app is available for download on Android and iOS smartphones.







# **Teleport Specifications**

Dimensions	43.00 x 75.85 x 38.85 mm (1.69 x 2.95 x 1.53")
Weight	80 g (2.82 oz)
Max. TX Power	19 dBm
Speed	300 Mbps
ESD/EMP Protection	± 24kV Air/Contact
Buttons	Reset
Antennas	(2) Dual-Band
Wi-Fi Standards	802.11 a/b/g/n
Wireless Security	WPA2-PSK AES/TKIP
Operating Temperature	14 to 131° F (-10 to 55° C)
Operating Humidity	5 to 95% Noncondensing
Certifications	FCC/CE/IC

## Supported Data Rates

802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b	1, 2, 5.5, 11 Mbps
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps



Dimensions	99.5 x 97.8 x 99.6 mm (3.91 x 3.85 x 3.92")
Weight	410 g (14.46 oz)
Max. TX Power	26 dBm
Radios	2
MIMO Chains	6
Speed	1750 Mbps
Networking Interface	Wi-Fi/Gigabit Ethernet (1) WAN, (4) LAN
Max. Power Consumption	11W
ESD/EMP Protection	± 24kV Air/Contact
Buttons	Reset
Antennas	(1) Dual-Band Antenna, Tri-Polarity
Display	40.6 mm (1.6") Diagonal, 240 x 240, 212 ppi, G+F Touch, Full Color
Wi-Fi Standards	802.11ac
Power Save	Supported
Wireless Security	WPA2-PSK AES/TKIP
Operating Temperature	14 to 131° F (-10 to 55° C)
Operating Humidity	5 to 95% Noncondensing
Certifications	FCC/CE/IC

# Supported Data Rates

802.11ac	13 Mbps to 1300 Mbps (MCS0 - MCS9, VHT 20/40/80)
802.11n	6.5 Mbps to 450 Mbps (MCS0 - MCS23, HT 20/40)
802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b	1, 2, 5.5, 11 Mbps
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps



Set-Top Box

AmpliFi Teleport

AmpliFi Router



# 24/7 Live Global Chat Support

device. Teleport allows you easy access while you are away

from the most important place - your home.

24/7 Live Global Chat Support within the AmpliFi app and also online at <a href="https://example.com">help.amplifi.com</a>

