


# V-IS10F-4T-2FC20-A/B

## MAIN FEATURES



**4 Port 10/100Mbps RJ45 +2 Port Fiber Uplink, Single mode, Single fiber, FC, 20KM, Dual Power DC12~58V, Each port support Max 30W, -40°C to +75°C**

**Input Voltage:** DC12~58V (Non-PoE)

**Operating Temperature:** -40°C~+75°C

**Shell:** IP40 protection, Fanless design

**Anti-static:** 8KV-15KV

## PRODUCT DESCRIPTION

This device is 2\*100Base-X FC Fiber port, Single mode, Single fiber 4\*10/100M Base-TX Industrial Ethernet Switches. Through the fanless heat dissipation circuit design, wide range of working environment temperature, high protection level and other technologies, it provides excellent industrial quality with high/low temperature resistance and lightning protection, and enhances the reliability and safety of industrial networks. It can better meet the deployment requirements of rail transit, safe city, intelligent transportation, outdoor monitoring and other harsh environments.

Also known as Industrial Ethernet Switch, which is an Ethernet switch device used in industrial control. Due to the adopted network standard, it is open, widely used, and inexpensive. It uses a transparent and unified TCP/IP protocol. The network has become the main communication standard in the field of industrial control.

**Scodena**

Industrial switches feature carrier-grade performance to withstand harsh environments. With a wide range of products and flexible port configurations, it can meet the needs of various industrial fields. The product features a wide temperature design with a protection rating of no less than IP30 and supports standard and proprietary ring redundancy protocols

## KEY FEATURES



Industrial protection



Wide range of operating temperature



Surge protection for power



Surge protection for Ethernet port



Dual Power Supply

## DIP SWITCH



1 C/D	Remote PD Reset
2 LGY	Standard/Non-standard PoE Mode
3 VLAN	Port Isolation
4 RST	Reset

## PRODUCT PARAMETERS

Description	Specifications
<b>Provider Mode Ports</b>	
Fixed port	2*100 Base-FX FC, 4*10/100Base-TX
Power interface	Phoenix terminal, redundant dual power supply
LED Indicators	PWR, OPT ,NMC, ALM
<b>DIP Switch</b>	
1 C/D	Remote PD Reset
2 LGY	Stand/Non-standard PoE Mode
3 VLAN	Port Isolation
4 RST	Reset
<b>Cable type &amp; Transmission distance</b>	
Twisted-pair	0-100m (CAT5e,CAT6)
Monomode optical fiber	20KM SMF
<b>Electrical Specifications</b>	
Input voltage	DC12-58V(Non-PoE)
Total Power consumption	Total power<6W(Non-PoE)
Voltage Alarm	Support
<b>Network Topology</b>	
Ring topology	Unsupport
Star topology	Support
Bus topology	Support
Tree Topology	Support
Hybrid topology	Support
<b>Layer 2 Switching</b>	
Switching capacity	14G
Packet forwarding rate	10.416Mpps
Mac address table	8K
Buffer	1M
Forwarding delay	<5us
MDX/MIDX	Support
Flow control	Support
Jumbo Frame	2K Bytes
WatchDog	Support
Port Isolation	Support
<b>Environment</b>	
Operating temperature	-40°C~+75°C The device is tested for 4 hours at temperatures in 85°C
Storage temperature	-40°C~+75°C

Relative humidity	5%~95% non-condensing
Thermal methods	Fanless design, natural cooling
MTBF	100,000 hours
<b>EMC &amp; INGRESS PROTECTION</b>	
IP Level	IP40
Surge protection of Power	IEC 61000-4-5 Level X (6KV/6KV) (8/20us)
Surge protection of Ethernet port	IEC 61000-4-5 Level X (4KV/4KV) (10/700us)
RS	IEC 61000-4-3 Level 3 (10V/m)
EFI	IEC 61000-4-4 Level 3 (1V/2V)
CS	IEC 61000-4-6 Level 3 (10V/m)
PFFM	IEC 61000-4-8 Level 4 (30A/m)
DIP	IEC 61000-4-11 Level 3 (10V)
ESD	IEC 61000-4-2 Level 4 (8K/15K)
Free fall	0.5m
<b>Mechanical Dimensions</b>	
Product size	143X104X48mm
Installation Method	DIN rail
Weight	0.6KG
<b>Authentication</b>	
Authentication	CCC/CE/FCC/RoHS
<b>Accessories</b>	
Accessories	Device, Terminals, Specification, Certificate, power adapter(optional)

## ORDERING INFORMATION

<b>Switch</b>	
Product number	Product description
V-IS10F-4T-2FC20-A	4 Port 10/100Mbps RJ45 +2 Port Fiber Uplink, Single mode, Single fiber, FC, 20KM, Dual Power DC12~58V, Each port support Max 30W, -40°C to +75° C
V-IS10F-4T-2FC20-B	4 Port 10/100Mbps RJ45 +2 Port Fiber Uplink, Single mode, Single fiber, FC, 20KM, Dual Power DC12~58V, Each port support Max 30W, -40°C to +75° C
<b>Package Contents</b>	
<ul style="list-style-type: none"> <li>• 1x Device</li> <li>• 1x Phoenix Terminal</li> <li>• 1x Qualified Certificate</li> <li>• 1x Instruction &amp; Warranty Card</li> </ul>	

## SIZE AND APPEARANCE

