

# CentreCOM<sup>®</sup> GS970EMX Series

## Gigabit Layer 3 Lite Access Switches

The Allied Telesis CentreCOM GS970EMX Series Layer 3 Lite switches provide Gigabit connectivity with Multi-Gigabit copper and 10 Gigabit fiber uplinks. They feature a comprehensive feature-set making them ideal for secure and cost-effective access in small to medium business networks.



### Overview

Allied Telesis GS970EMX Series provide high availability, security, and a basic L3 feature set. They enable Gigabit to the desktop with Multi-Gigabit and 10 Gigabit copper and fiber uplinks, making them ideal for the edge of modern business networks.

The compact fanless design of the 10, 20, and 28 port models provides silent operation for work area deployment.

### Network Management

The GS970EMX Series support the AlliedWare Plus<sup>™</sup> advanced operating system for consistent management across all devices. The industry-standard Command Line Interface (CLI) reduces time and cost, while the web-based Graphical User Interface (GUI) is built in for easy-to-use visual management.

### Network Security

Network security is guaranteed, with powerful control over network traffic types, secure management options, and other multi-layered security features built right in.

Network Access Control (NAC) gives unprecedented control over user access to the network, in order to mitigate threats to network infrastructure.

802.1x port-based authentication, in partnership with standards-compliant dynamic VLAN assignment, checks a user's adherence to network security policies and either grants access or offers remediation. Tri-authentication ensures the network is only accessed by known users and devices, and secure access is available for guests.

Protection from malicious network attacks is provided by security features such as DHCP snooping, STP root guard, BPDU protection, and access control lists. Each of these can be configured to perform a variety of actions upon detection of a suspected attack.

### Stackable

Create a VCStack<sup>™</sup> of up to four GS970EMX/20, 28, and 52 port switches with 40 Gbps of stacking bandwidth. VCStack provides a highly-available system in which network resources are spread out across stacked units, minimizing the impact should any link or unit fail.

### Reliability

The GS970EMX Series support Ethernet Protection Switched Ring (EPSRing<sup>™</sup>), which prevents loops in ring-based networks. EPSR offers rapid detection and extremely fast failover in the event of a link or node failure, with recovery in as little as 50 milliseconds.

The GS970EMX Series can act as the EPSR master with a premium license, ensuring resiliency in Ethernet ring-based networks.

### Comprehensive Security

As AMF Plus edge nodes, the GS970EMX Series is compatible with our AMF-Security solution, which enables a self-defending network. The AMF-Sec controller responds immediately to any internal malware threats by instructing the GS970EMX to isolate the affected part of the network, and quarantine the suspect device.

### ECO Friendly

The GS970EMX Series support Energy Efficient Ethernet, which automatically

reduces the power consumed by the switch whenever there is no traffic on a port.

The GS970EMX Series fanless models provide silent operation, which makes them ideal for desktop or work area deployment.

## Key Features

- ▶ AlliedWare Plus operating system
- ▶ Autonomous Management Framework Plus (AMF Plus) edge node
- ▶ Vista Manager EX compatible
- ▶ AMF-Security compatible
- ▶ 1/2.5/5/10 Multi-Gigabit copper uplink ports
- ▶ 1/10G SFP/SFP+ fiber uplink ports
- ▶ EPSRing<sup>™</sup> for resilient high-speed ring-based networks
- ▶ EPSR Master
- ▶ VCStack up to 4 units (20, 28, and 52 port models)
- ▶ Energy Efficient Ethernet
- ▶ Active Fiber Monitoring
- ▶ Static and dynamic routing
- ▶ Fanless for silent operation (10, 20, and 28 port models)
- ▶ Web-based Device GUI
- ▶ Multicast Source Discovery Protocol (MSDP)
- ▶ Link Monitoring
- ▶ NETCONF/RESTCONF with YANG data modelling

# GS970EMX Series | Gigabit Layer 3 Lite Access Switches

## Product Specifications

PRODUCT	10/100/1000T (RJ-45) COPPER PORTS	1/2.5/5/10G COPPER PORT	1/10G SFP+ PORT	TOTAL PORTS	STACKING PORTS	SWITCHING FABRIC	FORWARDING RATE
GS970EMX/10	8	1	1	10	-	56Gbps	41.6Mpps
GS970EMX/20	16	2	2	20	4	72Gbp	83.3Mpps
GS970EMX/28	24	2	2	28	4	128Gbp	95.2Mpps
GS970EMX/52	48	2	2	52	4	176Gbp	130.9Mpps

## Physical Specifications

PRODUCT	WIDTH X DEPTH X HEIGHT	MOUNTING	WEIGHT		PACKAGED DIMENSIONS
			UNPACKAGED	PACKAGED	
GS970EMX/10	263 x 179 x 38 mm (10.35 x 7.04 x 1.497 in)	Rack-mount	1.6 kg (3.53 lb)	2.97 kg (6.55 lb)	462 x 258 x 107 mm (18.19 x 10.15 x 4.21 in)
GS970EMX/20	341 x 231 x 44 mm (13.42 x 9.09 x 1.73 in)	Rack-mount	3.0 kg (6.61 lb)	4.42 kg (9.74 lb)	530 x 360 x 120 mm (20.86 x 14.17 x 4.72 in)
GS970EMX/28	341 x 231 x 44 mm (13.42 x 9.09 x 1.73 in)	Rack-mount	3.1 kg (6.84 lb)	4.42 kg (9.74 lb)	530 x 360 x 120 mm (20.86 x 14.17 x 4.72 in)
GS970EMX/52	441 x 323 x 44 mm (17.36 x 12.71 x 1.73 in)	Rack-mount	4.5 kg (9.92 lb)	6.20 kg (13.66 lb)	530 x 360 x 120 mm (20.86 x 14.17 x 4.72 in)

## Latency (microseconds)

PRODUCT	PORT SPEED				
	100MBPS	1GBPS	2.5GBPS	5GBPS	10GBPS
GS970EMX/10	6.22	3.68	3.24	2.86	1.73
GS970EMX/20	7.32	3.73	3.48	3.13	1.87
GS970EMX/28	7.18	3.71	3.39	3.04	1.82
GS970EMX/52	7.11	3.62	3.56	3.08	2.31

## Power and Noise Characteristics

PRODUCT	MAX POWER CONSUMPTION(W)	MAX HEAT DISSIPATION(BTU/H)	NOISE (DBA)
GS970EMX/10	21	71	Fanless
GS970EMX/20	28	96	Fanless
GS970EMX/28	33	114	Fanless
GS970EMX/52	52	181	45.4

## Specifications

### Performance

- Supports 10KB L2 jumbo frames for 2.5G connections, or 12KB for all other connection speeds (GS970EMX/10,20,28)
- Supports 10KB L2 jumbo frames for 1000M, 2.5G connections, or 12KB for 5G, 10G connection speeds (GS970EMX/52)
- Wire speed multicasting
- 4094 configurable VLANs
- Up to 16K MAC addresses
- 1GB DDR3 SDRAM, 256MB NAND flash memory
- Packet buffer memory: 2MB

### Reliability

- Modular AlliedWare Plus operating system
- Temperature and internal voltages. SNMP traps alert network managers in case of any failure

### Expandability

- Stack up to four units in a VCStack (GS970EMX/20, 28, and 52 port models only)
- Premium license for additional features

### Flexibility and Compatibility

- 10G SFP+ ports will support any combination of Allied Telesis 1000Mbps SFP and 10GbE SFP+ modules and direct attach cables listed in this document under Ordering Information
- The 1/2.5/5/10G Multi-Gigabit port enables flexible uplink options, and support for legacy cabling
- Port speed and duplex configuration can be set manually or by auto-negotiation

### Diagnostic Tools

- Built-In Self Test (BIST)
- Ping polling and traceroute for IPv4 and IPv6
- Optical Digital Diagnostic Monitoring (DDM)
- Find-me device locator
- Link Monitoring
- Automatic link flap detection and port shutdown
- Cable fault locator (TDR)
- Uni-Directional Link Detection (UDLD)
- Active Fiber Monitoring detects tampering on optical links

### IP Features

- RIP, OSPF, and Static routing for IPv4
- Device management over IPv6 networks with SNMP, Telnet, SSH
- IPv6 hardware ACLs
- Log to IPv6 hosts with Syslog
- DHCPv4 and v6 client

### Management

- Allied Telesis Autonomous Management Framework™ Plus (AMF Plus) enables powerful centralized management and zero-touch device installation and recovery
- Manage the GS970EMX Series switches with Vista Manager EX—our graphical single-pane-of-glass monitoring and management tool for AMF Plus networks, which also supports wireless and third party devices
- From AW+ 5.5.2-2, an AMF Plus license operating in the network provides all standard AMF network management and automation features, and also enables the AMF Plus intent-based networking features in Vista Manager EX (from version 3.10.1 onwards)

- AMF Security (AMF-Sec) enables a self-defending network—managing the GS970EMX (or other AMF Plus switches) to automatically block the spread of malware by quarantining suspect end devices
- NETCONF/RESTCONF northbound interface with YANG data modelling
- Industry-standard CLI with context-sensitive help
- Built-in text editor and powerful CLI scripting engine
- Comprehensive SNMP MIB support for standards-based device management
- Console management port on the front panel for ease of access
- Event-based triggers allow user-defined scripts to be executed upon selected system events
- Eco-friendly mode allows ports and LEDs to be disabled to save power
- USB interface allows software release files, configurations and other files to be stored for backup and distribution to other devices
- Front panel 7-segment LED provides at-a-glance status and fault information
- Web-based Graphical User Interface (GUI)

### Quality of Service

- IP precedence and DiffServ marking based on Layer 2, 3 and 4 headers
- Queue scheduling options for strict priority, weighted round robin or mixed scheduling
- Taildrop for queue congestion control
- Extensive remarking capabilities
- Policy-based QoS based on VLAN, port, MAC and general packet classifiers
- Type of Services (ToS) IP precedence and DiffServ marking based on layer 2, 3 and 4 headers

- ▶ Limit bandwidth per port or per traffic class down to 64kbps
- ▶ 8 priority queues with a hierarchy of high priority queues for real time traffic, and mixed scheduling, for each switch port
- ▶ Policy-based storm protection
- ▶ Wirespeed traffic classification with low latency essential for VoIP and real-time streaming media applications

### Resiliency Features

- ▶ EPSRing (Ethernet Protection Switched Rings) with Super Loop Protection (SLP) and enhanced recovery
- ▶ STP root guard
- ▶ Loop protection: thrash limiting and loop detection
- ▶ Dynamic link failover (host attach)
- ▶ Control Plane Prioritization (CPP) ensures the CPU always has sufficient bandwidth to process network control traffic
- ▶ VCSStack fast-failover minimizes network disruption
- ▶ SFP+ stacking ports can be configured as 10G Ethernet ports
- ▶ PVST+ compatibility mode
- ▶ BPDU forwarding

### Security Features

- ▶ MAC address filtering and MAC address lock-down
- ▶ Port-based learn limits (intrusion detection)
- ▶ Access Control Lists (ACLs) based on layer 3 and 4 headers
- ▶ Secure Copy (SCP)
- ▶ BPDU protection
- ▶ Network Access and Control (NAC) features manage endpoint security
- ▶ Dynamic VLAN assignment
- ▶ Tri-authentication: MAC-based, web-based and IEEE 802.1x
- ▶ DoS attack blocking and virus throttling
- ▶ DHCP snooping, IP source guard and Dynamic ARP Inspection (DAI)
- ▶ Strong password security and encryption
- ▶ Auth fail and guest VLANs
- ▶ Secure File Transfer Protocol (SFTP) client
- ▶ RADIUS and TACACS+ for Authentication, Authorization and Accounting (AAA)
- ▶ Bootloader can be password protected for device security
- ▶ Configurable ACLs for management traffic
- ▶ RADIUS group selection per VLAN or port

### VLAN Support

- ▶ Generic VLAN Registration Protocol (GVRP)
- ▶ Voice VLAN
- ▶ Private VLANs provide security and port isolation for multiple customers using the same VLAN

### Environmental Specifications

- ▶ Operating temperature range: 0°C to 50°C (32°F to 122°F)
- ▶ Storage temperature range: -25°C to 70°C (-13°F to 158°F)
- ▶ Operating relative humidity range: 5% to 90% non-condensing
- ▶ Storage relative humidity range: 5% to 95% non-condensing
- ▶ Operating altitude range: Up to 3,048 meters maximum (10,000 ft)

### Electrical Approvals and Compliances

- EMC:
- ▶ EN55032 class A
- EMI:
- ▶ FCC part15 Subpart B/ Class A
  - ▶ ICES-003:2016, Issue6 Class A
  - ▶ EN55032:2012 / AC: 2013 Class A
  - ▶ CISPR 32:2012 ClassA
  - ▶ RCM AS/NZS CISPR 32 : 2013 Class A
  - ▶ EN 61000-3-2
  - ▶ EN 61000-3-3
- EMS:
- ▶ EN 55024: 2010
  - ▶ EN 55035: 2017

### Safety Standards

- ▶ UL62368-1(cULus),
- ▶ EN/IEC62368-1(UL-CB/EU)
- ▶ EN/IEC 60825-1 (Laser Safety)
- ▶ ISO/IEC 15408
- ▶ CE
- ▶ EAC
- ▶ UKCA
- ▶ NOM

### Restrictions on Hazardous Substances (RoHS) Compliance

- ▶ EU RoHS compliant
- ▶ China RoHS compliant

## Standards and Protocols

### Authentication

- RFC 1321 MD5 Message-Digest algorithm
- RFC 1828 IP authentication using keyed MD5

### Cryptographic Algorithms

#### FIPS Approved Algorithms

- Encryption (Block Ciphers):
- ▶ AES (ECB, CBC, CFB and OFB Modes)
  - ▶ 3DES (ECB, CBC, CFB and OFB Modes)
- Block Cipher Modes:
- ▶ CCM
  - ▶ CMAC
  - ▶ GCM
  - ▶ XTS

Digital Signatures & Asymmetric Key Generation:

- ▶ DSA
- ▶ ECDSA
- ▶ RSA

Secure Hashing:

- ▶ SHA-1
- ▶ SHA-2 (SHA-224, SHA-256, SHA-384, SHA-512)

Message Authentication:

- ▶ HMAC (SHA-1, SHA-2(224, 256, 384, 512)

Random Number Generation:

- ▶ DRBG (Hash, HMAC and Counter)

### Non FIPS Approved Algorithms

- RNG (AES128/192/256)
- DES
- MD5

### Ethernet Standards

- IEEE 802.2 Logical Link Control (LLC)
- IEEE 802.3 Ethernet
- IEEE 802.3ab1000BASE-T
- IEEE 802.3ae10 Gigabit Ethernet
- IEEE 802.3azEnergy Efficient Ethernet (EEE)

- IEEE 802.3bz2.5GBASE-T and 5GBASE-T ("multi-gigabit")
- IEEE 802.3u 100BASE-X
- IEEE 802.3x Flow control - full-duplex operation
- IEEE 802.3z 1000BASE-X

### IPv4 Features

- RFC 768 User Datagram Protocol (UDP)
- RFC 791 Internet Protocol (IP)
- RFC 792 Internet Control Message Protocol (ICMP)
- RFC 793 Transmission Control Protocol (TCP)
- RFC 826 Address Resolution Protocol (ARP)
- RFC 894 Standard for the transmission of IP datagrams over Ethernet networks
- RFC 919 Broadcasting Internet datagrams
- RFC 922 Broadcasting Internet datagrams in the presence of subnets
- RFC 932 Subnetwork addressing scheme
- RFC 950 Internet standard subnetting procedure
- RFC 951 Bootstrap Protocol (BootP)
- RFC 1027 Proxy ARP
- RFC 1035 DNS client
- RFC 1042 Standard for the transmission of IP datagrams over IEEE 802 networks
- RFC 1071 Computing the Internet checksum
- RFC 1122 Internet host requirements
- RFC 1191 Path MTU discovery
- RFC 1256 ICMP router discovery messages
- RFC 1518 An architecture for IP address allocation with CIDR
- RFC 1519 Classless Inter-Domain Routing (CIDR)
- RFC 1542 Clarifications and extensions for BootP
- RFC 1591 Domain Name System (DNS)
- RFC 1812 Requirements for IPv4 routers
- RFC 1918 IP addressing
- RFC 2581 TCP congestion control
- RFC 3021 Using 31-bit prefixes on IPv4 point-to-point links

### IPv6 Features

- RFC 1981 Path MTU discovery for IPv6
- RFC 2460 IPv6 specification
- RFC 2464 Transmission of IPv6 packets over Ethernet networks
- RFC 2711 IPv6 router alert option
- RFC 3484 Default address selection for IPv6
- RFC 3587 IPv6 global unicast address format
- RFC 3596 DNS extensions to support IPv6
- RFC 4007 IPv6 scoped address architecture
- RFC 4193 Unique local IPv6 unicast addresses
- RFC 4213 Transition mechanisms for IPv6 hosts and routers
- RFC 4291 IPv6 addressing architecture
- RFC 4861 Neighbor discovery for IPv6
- RFC 4862 IPv6 Stateless Address Auto-Configuration (SLAAC)
- RFC 5014 IPv6 socket API for source address selection
- RFC 5095 Deprecation of type 0 routing headers in IPv6
- RFC 5175 IPv6 Router Advertisement (RA) flags option
- RFC 6105 IPv6 Router Advertisement (RA) guard

### Management

- AT Enterprise MIB including AMF Plus MIB and SNMP traps
- Optical DDM MIB
- SNMPv1, v2c and v3
- ANSI/TIA-1057 LLDP-Media Endpoint Detection
- IEEE 802.1ABLink Layer Discovery Protocol (LLDP)
- RFC 1155 Structure and identification of management information for TCP/IP-based Internets
- RFC 1157 Simple Network Management Protocol (SNMP)
- RFC 1212 Concise MIB definitions
- RFC 1213 MIB for network management of TCP/IP-based Internets: MIB-II
- RFC 1215 Convention for defining traps for use with the SNMP
- RFC 1227 SNMP MUX protocol and MIB
- RFC 1239 Standard MIB
- RFC 1724 RIPv2 MIB extension
- RFC 2578 Structure of Management Information v2 (SMIV2)

# GS970EMX Series | Gigabit Layer 3 Lite Access Switches

RFC 2579	Textual conventions for SMIv2
RFC 2580	Conformance statements for SMIv2
RFC 2674	Definitions of managed objects for bridges with traffic classes, multicast filtering and VLAN extensions
RFC 2741	Agent extensibility (AgentX) protocol
RFC 2819	RMON MIB (groups 1,2,3 and 9)
RFC 2863	Interfaces group MIB
RFC 3176	sFlow: a method for monitoring traffic in switched and routed networks
RFC 3411	An architecture for describing SNMP management frameworks
RFC 3412	Message processing and dispatching for the SNMP
RFC 3413	SNMP applications
RFC 3414	User-based Security Model (USM) for SNMPv3
RFC 3415	View-based Access Control Model (VACM) for SNMP
RFC 3416	Version 2 of the protocol operations for the SNMP
RFC 3417	Transport mappings for the SNMP
RFC 3418	MIB for SNMP
RFC 3635	Definitions of managed objects for the Ethernet-like interface types
RFC 3636	IEEE 802.3 MAU MIB
RFC 4022	MIB for the Transmission Control Protocol (TCP)
RFC 4113	MIB for the User Datagram Protocol (UDP)
RFC 4188	Definitions of managed objects for bridges
RFC 4292	IP forwarding table MIB
RFC 4293	MIB for the Internet Protocol (IP)
RFC 4318	Definitions of managed objects for bridges with RSTP
RFC 4502	RMON 2
RFC 4560	Definitions of managed objects for remote ping, traceroute and lookup operations
RFC 5424	The Syslog protocol

## Multicast Support

Bootstrap Router (BSR) mechanism for PIM-SM	
IGMP query solicitation	
IGMP snooping (IGMPv1, v2 and v3)	
IGMP snooping fast-leave	
IGMP/MLD multicast forwarding (IGMP/MLD proxy)	
MLD snooping (MLDv1 and v2)	
RFC 1112	Host extensions for IP multicasting (IGMPv1)
RFC 2236	Internet Group Management Protocol v2 (IGMPv2)
RFC 2715	Interoperability rules for multicast routing protocols
RFC 3376	IGMPv3
RFC 3618	Multicast Source Discovery Protocol (MSDP)
RFC 3810	Multicast Listener Discovery v2 (MLDv2) for IPv6
RFC 3956	Embedding the Rendezvous Point (RP) address in an IPv6 multicast address

RFC 3973	PIM Dense Mode (DM)
RFC 4541	IGMP and MLD snooping switches
RFC 4601	Protocol Independent Multicast - Sparse Mode (PIM-SM): protocol specification (revised)
RFC 4604	Using IGMPv3 and MLDv2 for source-specific multicast
RFC 4607	Source-specific multicast for IP

## Open Shortest Path First (OSPF)

OSPF link-local signaling	
OSPF MD5 authentication	
Out-of-band LSDB resync	
RFC 1245	OSPF protocol analysis
RFC 1246	Experience with the OSPF protocol
RFC 1370	Applicability statement for OSPF
RFC 1765	OSPF database overflow
RFC 2328	OSPFv2
RFC 2370	OSPF opaque LSA option
RFC 3101	OSPF Not-So-Stubby Area (NSSA) option
RFC 3509	Alternative implementations of OSPF area border routers
RFC 3623	Graceful OSPF restart
RFC 3630	Traffic engineering extensions to OSPF

## Quality of Service (QoS)

IEEE 802.1p	Priority tagging
RFC 2211	Specification of the controlled-load network element service
RFC 2474	DiffServ precedence for eight queues/port
RFC 2475	DiffServ architecture
RFC 2597	DiffServ Assured Forwarding (AF)
RFC 2697	A single-rate three-color marker
RFC 2698	A two-rate three-color marker
RFC 3246	DiffServ Expedited Forwarding (EF)

## Resiliency Features

IEEE 802.1AX	Link aggregation (static and LACP)
IEEE 802.1D	MAC bridges
IEEE 802.1s	Multiple Spanning Tree Protocol (MSTP)
IEEE 802.1w	Rapid Spanning Tree Protocol (RSTP)
IEEE 802.3ad	Static and dynamic link aggregation

## Routing Information Protocol (RIP)

RFC 1058	Routing Information Protocol (RIP)
RFC 2082	RIP-2 MD5 authentication
RFC 2453	RIPv2

## Security Features

SSH remote login	
SSLv2 and SSLv3	
TACACS+ Accounting, Authentication and Authorization (AAA)	
IEEE 802.1X	Authentication protocols (TLS, TTLS, PEAP and MD5)
IEEE 802.1X	Multi-suplicant authentication
IEEE 802.1X	Port-based network access control

RFC 2560	X.509 Online Certificate Status Protocol (OCSP)
RFC 2818	HTTP over TLS ("HTTPS")
RFC 2865	RADIUS authentication
RFC 2866	RADIUS accounting
RFC 2868	RADIUS attributes for tunnel protocol support
RFC 2986	PKCS #10: certification request syntax specification v1.7
RFC 3546	Transport Layer Security (TLS) extensions
RFC 3579	RADIUS support for Extensible Authentication Protocol (EAP)
RFC 3580	IEEE 802.1x RADIUS usage guidelines
RFC 3748	PPP Extensible Authentication Protocol (EAP)
RFC 4251	Secure Shell (SSHv2) protocol architecture
RFC 4252	Secure Shell (SSHv2) authentication protocol
RFC 4253	Secure Shell (SSHv2) transport layer protocol
RFC 4254	Secure Shell (SSHv2) connection protocol
RFC 5246	Transport Layer Security (TLS) v1.2
RFC 5280	X.509 certificate and Certificate Revocation List (CRL) profile
RFC 5425	Transport Layer Security (TLS) transport mapping for Syslog
RFC 5656	Elliptic curve algorithm integration for SSH
RFC 6125	Domain-based application service identity within PKI using X.509 certificates with TLS
RFC 6614	Transport Layer Security (TLS) encryption for RADIUS
RFC 6668	SHA-2 data integrity verification for SSH

## Services

RFC 854	Telnet protocol specification
RFC 855	Telnet option specifications
RFC 857	Telnet echo option
RFC 858	Telnet suppress go ahead option
RFC 1091	Telnet terminal-type option
RFC 1350	Trivial File Transfer Protocol (TFTP)
RFC 1985	SMTP service extension
RFC 2049	MIME
RFC 2131	DHCPv4 client
RFC 2132	DHCP options and BootP vendor extensions
RFC 2616	Hypertext Transfer Protocol - HTTP/1.1
RFC 2821	Simple Mail Transfer Protocol (SMTP)
RFC 2822	Internet message format
RFC 3315	DHCPv6 client
RFC 3396	Encoding long options in DHCPv4
RFC 3633	IPv6 prefix options for DHCPv6
RFC 3646	DNS configuration options for DHCPv6
RFC 4330	Simple Network Time Protocol (SNTP) version 4
RFC 4954	SMTP service extension for authentication
RFC 5905	Network Time Protocol (NTP) version 4

## VLAN Support

IEEE 802.1Q	Virtual LAN (VLAN) bridges
IEEE 802.1v	VLAN classification by protocol and port
IEEE 802.3ac	VLAN tagging

## Feature Licenses

NAME	DESCRIPTION	INCLUDES	STACK LICENSING
AT-FL-G97EMX-01	GS970EMX Premium license	<ul style="list-style-type: none"><li>▶ Static Route<sup>1</sup> (128 routes)</li><li>▶ RIP<sup>1</sup> (256 routes)</li><li>▶ OSPFv2<sup>1</sup> (128 routes)</li><li>▶ PIMv4-SM, DM and SSM v4</li><li>▶ EPSR Master<sup>2</sup></li></ul>	<ul style="list-style-type: none"><li>▶ One license per stack member</li></ul>

<sup>1</sup> The standard switch software supports 16 Static, RIP, and OSPF routes

<sup>2</sup> The standard switch software supports EPSR transit mode



## GS970EMX Series | Gigabit Layer 3 Lite Access Switches

### Ordering Information

Model availability can vary between regions. Please check to see which models are available in your region.

#### AT-GS970EMX/10-xx

8-port 10/100/1000T switch with 1x 1/2.5/5/10 Gigabit copper uplink, 1x SFP/SFP+ slot, and a single fixed power supply

#### AT-GS970EMX/20-xx

16-port 10/100/1000T switch with 2x 1/2.5/5/10 Gigabit copper uplinks, 2x SFP/SFP+ slots, and a single fixed power supply

#### AT-GS970EMX/28-xx

24-port 10/100/1000T switch with 2x 1/2.5/5/10 Gigabit copper uplinks, 2x SFP/SFP+ slots, and a single fixed power supply

#### AT-GS970EMX/52-xx

48-port 10/100/1000T switch with 2x 1/2.5/5/10 Gigabit copper uplinks, 2x SFP/SFP+ slots, and a single fixed power supply

Where xx = 10 for US power cord  
30 for UK power cord  
40 for Australian power cord  
50 for European power cord

#### AT-RKMT-J05

Rack Mount Tray for GS970EMX/10

#### AT-RKMT-J13

Rack Mount Kit for GS970EMX/20 and GS970EMX/28

#### AT-RKMT-SL01

Sliding rackmount kit for GS970EMX/52

#### AT-BRKT-J23

Wall mount kit for GS970EMX/10

#### AT-BRKT-J24

Wall mount kit for GS970EMX/20 and GS970EMX/28

#### AT-VT-Kit3

Management Cable (USB to Serial Console)

#### AT-STND-J03

Stand-kit for GS970EMX/20 and GS970EMX/28

### 10G SFP+ Modules

Any 10G SFP+ module or cable can be used for stacking with the front panel 10G ports

#### AT-SP10SR

10GSR 850 nm short-haul, 300 m with MMF

#### AT-SP10SR/I

10GSR 850 nm short-haul, 300 m with MMF industrial temperature

#### AT-SP10LRa/I

10GLR 1310 nm medium-haul, 10 km with SMF industrial temperature

#### AT-SP10TM

1G/2.5G/5G/10G, 100m copper, TAA<sup>3</sup>

#### AT-SP10BD10/I-12

10 GbE Bi-Di (1270 nm Tx, 1330 nm Rx) fiber up to 10 km industrial temperature, TAA<sup>3</sup>

#### AT-SP10BD10/I-13

10 GbE Bi-Di (1330 nm Tx, 1270 nm Rx) fiber up to 10 km industrial temperature, TAA<sup>3</sup>

#### AT-SP10BD20-12

10 GbE Bi-Di (1270 nm Tx, 1330 nm Rx) fiber up to 20 km, TAA<sup>3</sup>

#### AT-SP10BD20-13

10 GbE Bi-Di (1330 nm Tx, 1270 nm Rx) fiber up to 20 km, TAA<sup>3</sup>

#### AT-SP10TW1

1 meter SFP+ direct attach cable

#### AT-SP10TW3

3 meter SFP+ direct attach cable

### 1000Mbps SFP Modules

#### AT-SPSX

1000SX GbE multi-mode 850 nm fiber up to 550 m

#### AT-SPLX10a

1000LX GbE single-mode 1310 nm fiber up to 10 km

#### AT-SPLX10/I

1000LX GbE single-mode 1310 nm fiber up to 10 km, industrial temperature

#### AT-SPLX40

1000LX GbE single-mode 1310 nm fiber up to 40 km

#### AT-SPBD10-13

1000LX (LC) GbE Bi-Di (1310 nm Tx, 1490 nm Rx) fiber up to 10 km

#### AT-SPBD10-14

1000LX (LC) GbE Bi-Di (1490 nm Tx, 1310 nm Rx) fiber up to 10 km

#### AT-SPBD20-13/I

1000BX GbE Bi-Di (1310 nm Tx, 1490 nm Rx) fiber up to 20 km

#### AT-SPBD20-14/I

1000BX GbE Bi-Di (1490 nm Tx, 1310 nm Rx) fiber up to 20 km

#### AT-SPBD40-13/I

1000LX (LC) GbE single-mode Bi-Di (1310 nm Tx, 1490 nm Rx) fiber up to 40 km, industrial temperature

#### AT-SPBD40-14/I

1000LX (LC) GbE single-mode Bi-Di (1490 nm Tx, 1310 nm Rx) fiber up to 40 km, industrial temperature

#### AT-SPTXc

10/100/1000 TX (RJ45), up to 100 m

<sup>3</sup> Trade Act Agreement compliant