



TL-R1200S-RP

JBOD Connection Interface	SATA
Drive Bay	12 x 3.5-inch The system is shipped without HDD. For the HDD compatibility list, please visit https://www.qnap.com/compatibility/
Drive Compatibility	3.5-inch bays: 3.5-inch SATA 6Gb/s, 3Gb/s hard disk drives 2.5-inch SATA 6Gb/s, 3Gb/s solid state drives You can only use one disk type (HDD or SSD) in a RAID group. Combining different types of disk in one RAID group is not supported.
Hot-swappable	Yes
Form Factor	2U Rackmount
Host Interface	3 x SFF-8088
LED Indicators	HDD 1-12, Status, Link, Fan error
Buttons	Power switch
Dimensions (HxWxD)	88.6 × 482 × 562.5 mm Excludes ear hook and the protruding part of the Power Supply Unit.
Weight (Net)	13.17 kg
Weight (Gross)	15.22 kg
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	250W(x2) PSU, 100 - 240V
Power Consumption: Operating Mode, Typical	73.7 W Tested fully populated with Seagate ST6000NM0024 hard drives.
Fan Mode Switch	Yes (Auto, high, medium, low)

Fan	2 x 70mm, 12VDC
System Warning	Buzzer
Kensington Security Slot	Yes
QTS / QuTS hero	Yes
Windows	Yes
Ubuntu	Yes
Standard Warranty	3

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.