

Datasheet

VSTek VS-SG124P-4G 24+2+2 port full giga 400W POE Switch



Product Features

- 24*10/100/1000mbps POE port;2*1000Mbps Uplink 2*10/100/1000mbps SFP
- 100m Distance
- Support IEEE802.3AF/AT
- Whole Power:400W (52V 7.7A)
- All port supported by MDI/MDIX auto flip and self negotiation
- Supply 26*10/100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. power supply reached 30W.

Application

- Wireless Access Point
- IP Camera
- IP Phone
- Computer Networks

Industry-specific attributes

Model	24+2+2 port full giga 400W POE Switch
Model No.	VS-SG124P-4G
POE Port	1 to 24 port support 1000Mbps IEEE802.3af/at
SFP port	25th-28th port support 1000Mbps
PoE output	15.4W/30W IEEE802.3af/at
PoE whole power	≤400W(52V 7.7A)
PoE type	End-span
Power distance	≤100m
Network Standard	IEEE 802.3、 IEEE802.3u、 802.3x、 802.3af/at
Network Medium	100/1000BASE-TX: 5 class and above non shielded twisted pair
Switch capability	56Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T: 14880PPS/port 100BASE-tx: 148800pps/port 1000BASE-tx: 1488000pps/port
MAC Address	8K MAC address table
Port function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Working Environment	Working Temperature: -10°-- 55°C
Input power	AC110-240V 50/60HZ
Weight	2.9kg
Size	440mm*284mm*45mm(L*W*H)