

Datasheet

VSTek VS-SF124P-4G 24+2+2 Port 400W POE Switch (Built-in)



Product Features

- 24*10/100Mbps POE port; 2*10/100/1000Mbps UP Link; 2*1000Mbps SFP.
- 100m Distance.
- Support IEEE 802.3AF/AT.
- Whole Power: 400W (52V - 7.7A).
- All port supported by MDI/MDIX auto flip and self-negotiation.
- Supply 28*10/100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. Power supply reached 30W.

Application

- Wireless Access Point
- IP Camera
- IP Phone
- Computer Networks

Industry-specific attributes

Product	24+2+2 port 400W POE switch(Built-in)
Model	VS-SF124P-4G
POE Port	1 to 24 port support 100mbps IEEE802.3af/at
UP link port	25th-28th port support 1000Mbps
PoE output	15.4W/30W IEEE802.3af/at
PoE whole power	≤400W (52V - 7.7A)
PoE type	End-span
Power distance	≤100m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	100/1000BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤100m
Switch capability	12.8Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T: 14880pps/port 100BASE-tx: 148800pps/port 1000BASE-T: 1488000pps/port
MAC Address	8K MAC address table
Port function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Indicator	LINK/ACT. 100Mbps; POE Status indicator; POWER indicator
Working Environment	Working Temperature: -10°-- 55°C
Input power	AC100-240V 50/60HZ
Weight	4.2kg
Size	440mm*285mm*44mm(L*W*H)